



TYPICAL SECTION

NOT TO SCALE

NOTES:

1. IF APPROVED BY THE COMMUNITY DEVELOPMENT DIRECTOR OR PUBLIC WORKS DIRECTOR SLOPE MAY VARY FROM 1% MIN. TO 5% MAX. TO MATCH EXISTING CONDITIONS AND TO FACILITATE JOINS. IF MIN. AND MAX. SLOPES CAN NOT BE MET, OFFSET THE FLOW LINE FROM CENTERLINE.
2. SMOOTH TROWEL 8" WIDE FLOWLINE IN CONCRETE GUTTER.
3. EXPANSION JOINTS IN GUTTER SHALL BE INSTALLED AT 40'-50' INTERVALS WITH FOUR NO.4 SMOOTH DOWELS (18" LONG).
4. WEAKENED PLANE JOINTS IN GUTTER SHALL BE INSTALLED AT 20'-25' INTERVALS.
5. T: THICKNESS OF CRUSHED AGGREGATE BASE (CAB) OR CRUSHED MISCELLANEOUS BASE (CMB).

CITY OF TORRANCE

DATE ISSUED

SEPT 2006

TYPICAL SECTION ALLEY

ROBERT J. BESTE
PUBLIC WORKS DIRECTOR
R.C.F. NO. 50737

STANDARD NO.

T101

SHEET 1 OF 1