



PERPENDICULAR CONSTRUCTION PARALLEL CONSTRUCTION

BASIC SEPARATION STANDARDS

- 1. PARALLEL CONSTRUCTION: THERE SHALL BE AT LEAST 10 FEET HORIZONTAL CLEARANCE BETWEEN PRESSURE DOMESTIC WATER MAINS AND SEWER LINES.
- 2. PERPENDICULAR CONSTRUCTION (CROSSING): PRESSURE WATER MAINS SHALL BE AT LEAST ONE FOOT ABOVE SANITARY SEWER LINES WHERE THESE LINES MUST CROSS.
- 3. SPECIAL PROVISIONS: ALTERNATE CONSTRUCTION CRITERIA WHERE THE BASIC SEPARATION STANDARDS CANNOT BE ATTAINED ARE SHOWN BELOW:

ZONE	SEWER CONSTRUCTION (EXISTING WATER)	
В	EXTRA STRENGTH V.C.P. WITH COMPRESSION JOINTS. APPROVED ALTERNATES.	
C/D	1) A CONTINUOUS SECTION OF DUCTILE IRON PIPE WITH HOT DIP BITUMINOUS COATING. 2) APPROVED ALTERNATES.	
Α	NO CONSTRUCTION WITHOUT APPROVAL OF TORRANCE MUNICIPAL WATER DEPARTMENT AND STATE DEPARTMENT OF HEALTH SERVICES.	
Р	CONSTRUCTION WITHIN THIS AREA PROHIBITED.	

	CITY OF TORRANCE	
DATE ISSUED	SEWER AND WATER	STANDARD NO
02 JUL 2008	SEPARATION REQUIREMENTS	T206
	ROBERT J. BESTE PUBLIC WORKS DIRECTOR R.C.E. NO. 50737	SHEET 1 OF