



BLDG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW
2	08.31.21	ISSUED FOR PLAN CHECK

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:

ELECTRICAL SITE PLAN

SHEET NO:

ELECTRICAL SCOPE OF WORK


PROPOSED ELECTRICAL SERVICE UPGRADE OF AN EXISTING SINGLE STORY COMMERCIAL STRUCTURE OF APPROXIMATELY 4,500 SF WITH ON GRADE PARKING. AN EXPANSION FOR DORMITORIES IS PROPOSED INCREASING THE NEW BUILDING TOTAL TO 4,825 SF.

THE EXISTING STANDBY GENERATOR SET SYSTEM SHALL REMAIN. SPARE CAPACITY IS AVAILABLE FOR THE MINOR INCREASE IN CONNECTED LOADS.

THE EXISTING MANUAL OFF-SITE GENERATOR SET SYSTEM SHALL REMAIN AND BE SIZED TO INCLUDE NEW AND EXISTING MECHANICAL SYSTEM LOADS.

EXISTING UTILITY POLE #1035956E
EQUIPPED WITH 1 BUCKET STYLE TRANSFORMER
FEEDS 'MS' VIA UNDERGROUND CONDUIT (TO BE VERIFIED)
- TO REMAIN AND SERVICE TO BE REDESIGNED.

- TO REMAIN AND SERVICE TO BE REDESIGNED



SITE PLAN REFERENCE NOTES:

- 1 MAINTAIN MINIMUM CODE REQUIRED WORKING SPACE CLEARANCE OF 3'-0" ABOUT ELECTRICAL EQUIPMENT PER NEC ARTICLE 110.26.
- 2 PROVIDE AND INSTALL A CONCRETE HOUSEKEEPING PAD FOR THE MAIN SERVICE SWITCHGEAR. HEIGHT OF PAD TO BE FIELD VERIFIED TO ALLOW TOP EXIT OF FEEDERS AND BRANCH CIRCUITS AND MEET ALL NEC 110.26 REQUIREMENTS. SEE SHEET E302 FOR DETAILS.
- 3 PROVIDE AND INSTALL VEHICULAR PROTECTION BARRIERS AROUND 3 SIDES OF THE NEW MAIN SERVICE SWITCHGEAR PER DWP REQUIREMENTS. MAINTAIN SPACING REQUIREMENTS PER SCE CONSTRUCTION STANDARDS.
- 4 FIELD VERIFY ALL REQUIREMENTS OF NEW SERVICE WITH SCE AND THE AHJ PRIOR TO START OF CONSTRUCTION AND INSTALLATION OF NEW WORK. REPORT ANY NEW FINDINGS TO ENGINEER OF RECORD. EXISTING SERVICE TO REMAIN ENERGIZED WHILE NEW SERVICE IS BEING INSTALLED. CONTRACTOR TO COORDINATE SWITCH OVER WITH OWNER'S REP, CITY AND UTILITY COMPANY TO MINIMIZE DOWNTIME.
- 5 THE EXISTING SINGLE PHASE SERVICE METERING COMPARTMENT AND ZINSCO SWITCHBOARD ARE TO BE DEMOLISHED, INCLUDING EXISTING FEEDER CONDUIT. FIELD VERIFY ANY EXISTING CIRCUITS TO REMAIN AND REPORT TO ENGINEER OF RECORD PRIOR TO ROUGH-IN SO THAT CIRCUITS CAN BE ROUTED TO NEW 1-PHASE 3-WIRE POWER DISTRIBUTION SYSTEM.
- 6 CONTRACTOR SHALL CONTACT UTILITY COMPANY TO REMOVE EXISTING METER SOCKET AND DISCONNECT THE UTILITY METERING.
- 7 PROVIDE AND INSTALL A RECEPTACLE AND ENCLOSURE THAT IS WEATHERPROOF AND IS LISTED AS "EXTRA DUTY". THE RECEPTACLE SHALL BE LISTED AS WEATHER RESISTANT TYPE WITH INTEGRAL GFCI PROTECTION. LOCATION SHALL BE WITHIN 50' OF ALL ELECTRICAL SERVICE EQUIPMENT.
- 8 CONFIRM SIZE AND NUMBER OF UTILITY CONDUITS WITH RESPECTIVE UTILITY COMPANY REPRESENTATIVE PRIOR TO INSTALLATION. SEE SHEET E600 FOR ADDITIONAL REQUIREMENTS.
- 9 THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR IDENTIFYING ALL EXISTING UNDERGROUND CONDUITS, UTILITIES AND LINES PRIOR TO ANY WORK. SEE DEMOLITION NOTES ON SHEET E200 FOR REQUIREMENTS TO MAINTAIN CIRCUIT CONTINUITY TO ALL EXISTING BRANCH CIRCUITS THAT ARE TO REMAIN. CONTACT DIG ALERT PER SCE AND CITY REQUIREMENTS FOR FIELD MARKING.
- 10 PROVIDE AND INSTALL A NEW RACEWAY PER SCE REQUIREMENTS WITH A STUB OUT OF UTILITY CONDUIT +24" PAST PROPERTY LINE. CONFIRM INDICATED POINT OF CONNECTION (POC) WITH SCE PRIOR TO BID. CONFIRM FINAL LOCATION AND ROUTING WITH SERVICE PLANNER PRIOR TO TRENCHING. SEE UTILITY COMPANY CONSTRUCTION DOCUMENTS.

SHEET INDEX

E100 - ELECTRICAL SITE PLAN
E200 - SYMBOLS AND NOTES
E201 - LIGHT FIXTURE SCHEDULE
E300 - NEW SINGLE LINE DIAGRAM AND DETAILS
E301 - EXISTING SINGLE LINE DIAGRAM (REFERENCE ONLY *F.V.)
E302 - MAIN SERVICE ELEVATION AND DETAILS
E303 - GROUNDING ELECTRODE CONDUCTOR SYSTEM
E304 - SINGLE LINE CALCULATIONS AND DETAILS
E400 - POWER AND SIGNAL PLAN
E401 - LIGHTING PLAN
E402 - ALARM LIGHTING PLAN
E403 - ROOF PLAN
E500 - PANEL SCHEDULES
E600 - SCE DETAILS AND SERVICE COMMITMENT LETTER
E601 - SCE MAP AND DETAILS
E602 - SCE MAP AND DETAILS
E700 - ELECTRICAL CONSTRUCTION SPECIFICATIONS
E800 - T24 CALCULATIONS
E801 - T24 CALCULATIONS

UTILITY SERVICE COORDINATION

POWER	
NAME	JESUS FERNANDO FERNANDEZ 'JESSE'
COMPANY	SCE SERVICE PLANNER
ADDRESS	SOUTH BAY DISTRICT
PHONE #	(310) 783-9389; MOBILE # (310) 502-0457
E-MAIL	Jesus.F.Fernandez@sce.com
CONTRACTOR TO CONTACT ABOVE REPRESENTATIVE TO CONFIRM EXISTING UTILITY SERVICE ARRANGEMENTS AND SCHEDULE TEMPORARY AND PERMANENT SERVICE CONDITION.	

GENERAL NOTES

- IT IS THE INTENT OF THESE PLANS AND SPECIFICATIONS THAT A COMPLETE AND WORKABLE ELECTRICAL INSTALLATION BE PROVIDED FOR ALL THE EQUIPMENT DESCRIBED OR SHOWN AS BEING IN THIS CONTRACT. FURNISH ALL LABOR AND TOOLS NECESSARY TO INSTALL ALL APPARATUS, MATERIALS AND EQUIPMENT IN A FASHION COMPLYING WITH ALL APPLICABLE CODES, INCLUDING ITEMS REQUIRED BUT NOT NORMALLY SHOWN, SUCH AS LAMPS, COUPLINGS, HANGERS, BRACKETS, CLAMPS, BOXES, CONNECTORS AND HARDWARE. REFER ALSO TO WRITTEN SPECIFICATIONS FOR GENERAL, MECHANICAL AND ELECTRICAL SECTIONS.
- PROCURE ALL PERMITS FROM LEGALLY CONSTITUTED AUTHORITIES, ARRANGE FOR ALL INSPECTIONS AND PAY ALL COSTS FOR FEES AND TESTS IN CONNECTION THEREWITH. COMPLY WITH CALIFORNIA BUILDING CODES: NOTHING IN THESE PLANS AUTHORIZES DEVIATION FROM APPLICABLE CODES.
- DETERMINE EXACT ROUTING OF CONCEALED FEEDERS AND BRANCH HOMERUNS IN COOPERATION WITH OTHER TRADES TO SIMPLIFY INSTALLATION WHEREVER POSSIBLE BUT SUBJECT TO APPROVAL OF ARCHITECT FOR VISUAL AND STRUCTURAL REASONS.
- PROVIDE A CODE APPROVED DISCONNECT SWITCH OR BREAKER WITHIN SIGHT OF EVERY MOTOR AND FEED MOTORS NOT EQUIPPED WITH "BUILT IN" PROTECTION THROUGH A MAGNETIC OR MANUAL STARTER WITH OVERLOAD HEATERS SIZED TO COMPLY WITH MOTOR MANUFACTURER'S RECOMMENDATIONS AND APPLICABLE CODES.
- FOR CONNECTIONS TO EXHAUST FANS, PUMPS, COMPRESSORS, SPACE HEATERS, WATER HEATERS, ADJUSTABLES, SOLENOID VALVES AND OTHER MECHANICAL EQUIPMENT AND FOR CONDUITS AND WIRE REQUIRED, BUT NOT NECESSARILY SHOWN ON THESE DRAWINGS, REFER TO MECHANICAL PLANS AND DETERMINE EXACT LOCATIONS UNDER DIRECTION OF THE MECHANICAL CONTRACTOR.
- DO NOT RUN ANY CONDUIT IN SLAB IF ITS OUTSIDE DIAMETER EXCEEDS 1/3 THE THICKNESS OF THE SLAB. LOCATE CONDUITS WITHIN THE MIDDLE OF THE SLAB. WHERE CONDUITS ARE GROUDED IN PARALLEL RUNS, SPACE THEM 3" OR MORE APART. WHERE CONDUITS CROSS EACH OTHER, THICKEN SLAB PROPORTIONATELY OVER A HORIZONTAL AREA EQUAL TO TEN TIMES THE DIAMETER OF THE LARGEST CONDUIT. REFER ALSO TO DETAILS SHOWN.
- FOR CIRCUITS FED THROUGH FLOURESCENT FIXTURE CHANNELS AND FEEDS TO RECESSED INCANDESCENT FIXTURES, USE INSULATED WIRE OF MINIMUM 90 DEG. CELSIUS RATING.
- IN EACH CONDUIT WITHOUT CONDUCTORS, PROVIDE ONE #12 TW COPPER PULL-WIRE WITH A TAG IDENTIFYING LOCATION OF OPPOSITE END.
- SIZE OUTLET BOXES IN CONFORMITY WITH CODE FOR NUMBER AND GAUGE OF CONDUCTORS THEREIN, EXCEPT WHERE NOTED TO BE LARGER. MINIMUM BOX SIZE SHALL BE 4" SQUARE BY 1-1/2" DEEP. OUTLET BOXES ON OPPOSITE SIDES OF WALLS OR PARTITIONS MUST BE SEPARATED BY A HORIZONTAL DISTANCE OF 24".
- EXAMINE PLANS TO DISCERN CEILINGS WITH A FIRE RATING OF ONE HOUR OR MORE. PROVIDE A ONE-HOUR FIRE-RATED ENCLOSURE OVER EACH LIGHT FIXTURE RECESSED THEREIN.
- AT THE TIME OF DESIGN UTILITY REQUIREMENTS HAVE NOT BEEN FINALLY CONFIRMED, MAKE FULL ALLOWANCE IN BID FOR ALL SERVICE COSTS LEVIED BY UTILITIES, INCLUDING CABLE COSTS AND ALL CONTINGENCIES NECESSARY TO COVER COSTS OF FINAL SERVICE CONNECTIONS AS REQUIRED. HANDLE ALL ARRANGEMENTS AND COSTS FOR TEMPORARY CONSTRUCTION POWER WHETHER FROM PORTABLE GENERATOR OR UTILITY COMPANY UNLESS OTHERWISE DESCRIBED IN "SPECIAL CONDITIONS".
- NO PIPING, DUCTS, OR EQUIPMENT FOREIGN TO ELECTRICAL EQUIPMENT SHALL BE PERMITTED TO BE INSTALLED, ENTER OR PASS THROUGH OR ABOVE THE REQUIRED WORK SPACE OF THE ELECTRICAL EQUIPMENT.
- "EXIT" SIGNS SHALL NOT BE USED AS JUNCTION BOXES. PROVIDE A SEPARATE J-BOX AT EACH "EXIT" SIGN LOCATION FOR MOUNTING PURPOSES AND FOR "THROUGH" & SIGN "PIGTAIL WIRING.
- ANY POWER OUTAGES SHALL BE APPROVED BY THE USER OF THE FACILITY. A FORTY-EIGHT HOUR WRITTEN NOTICE SHALL BE GIVEN FOR ANY OUTAGE REQUEST.
- VERIFY EXACT LOCATION OF OUTLETS, SWITCHES, EQUIPMENT, ETC WITH PROJECT MANAGER PRIOR TO INSTALLATION. OWNER RESERVES THE RIGHT TO RELOCATE ANY UNINSTALLED OUTLET IN ANY DIRECTION (10'-0" MAXIMUM) WITHOUT CHANGE IN CONTRACT PRICE PRIOR TO INSTALLATION.
- ALL LINE VOLTAGE WIRING SHALL BE MINIMUM #12 CU THHN/THWN. ALL NEW WIRING SHALL BE COPPER WITH "THHN" OR "THWN" 600-VOLT INSULATION. COLOR CODE ALL BRANCH CIRCUIT WIRING.
- ELECTRICAL BOXES OR FITTINGS SHALL BE FLUSH WITH FINISH SURFACE OR RECESSED NO MORE THAN 1/4 INCH IN NON-COMBUSTIBLE WALLS OR CEILING.
- ALL OUTLETS & DEVICES SHALL BE FLUSH WITH WALL, UNLESS OTHERWISE NOTED AS SURFACE MOUNTED.
- CONTRACTOR SHALL CORE DRILL, SAW CUT, PATCH TO MATCH ADJACENT SURFACES, AND PAINT ALL EXPOSED CONDUITS & BOXES TO MATCH ROOM FINISH.
- ALL SWITCHES SHALL BE INSTALLED LESS THAN 48" ABOVE FINISH FLOOR. ALL RECEPTACLES SHALL BE INSTALLED NO LOWER THAN 15" A.F.F.
- PIPES, CONDUITS AND DUCTS SHALL NOT PENETRATE INTO OR THROUGH STAIRWELL OR STAIR VESTIBULE EXIT ENCLOSURE PER U.B.C. 1005.3.3.5.
- ALL ELECTRICAL EQUIPMENT SHALL BE LISTED BY A CITY OF TORRANCE RECOGNIZED TESTING LABORATORY OR APPROVED BY THE BUILDING DEPARTMENT.
- ALL WORK TO COMPLY WITH 2019 CALIFORNIA ELECTRICAL CODE.
- PROVIDE U.L. LISTED GFI EQUIPMENT AND INSURE PROPER OPERATION PER CEC 110.10

CONTRACTOR NOTES

- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO INSURE THAT ALL APPLICABLE SAFETY LAWS ARE STRICTLY ENFORCED AND TO MAINTAIN A SAFE CONSTRUCTION PROJECT.
- THE CONTRACTOR SHALL REPAIR AND/OR REPAINT ALL AREAS DAMAGED BY CONSTRUCTION AND FINISH TO MATCH EXISTING ADJACENT SURFACES.
- THE CONTRACTOR SHALL SUBMIT "AS BUILT" DRAWINGS UPON COMPLETION OF CONSTRUCTION.
- DAILY AND UPON COMPLETION OF WORK, CONTRACTOR SHALL REMOVE DEBRIS, RUBBISH, WASTE, AND SURPLUS MATERIAL FROM PREMISES.
- THE CONTRACTOR SHALL PROTECT AND COVER ALL FIXTURES AND EQUIPMENT IN AREAS AFFECTED BY WORK AND UPON COMPLETION OF WORK SHALL THOROUGHLY CLEAN ALL FIXTURES, EQUIPMENT, WALLS, CEILING, FLOOR AND HARDWARE.

ALL ELECTRICAL EQUIPMENT SHALL BE LABELED, LISTED, OR CERTIFIED BY A NATIONALLY RECOGNIZED TESTING LABORATORY ACCREDITED BY THE UNITED STATES OCCUPATIONAL SAFETY HEALTH ADMINISTRATION

ALL ELECTRICAL WORK SHALL BE DESIGNED PER (LOCAL AHJ) ELECTRICAL CODE, 2019 CALIFORNIA ELECTRICAL CODE, 2017 NATIONAL ELECTRICAL CODE, AND 2019 BUILDING ENERGY EFFICIENCY STANDARDS

SYMBOLS REPRESENT EQUIPMENT & OUTLET BOXES TO WHICH CONDUIT & WIRE IS RUN FOR CONNECTION TO FIXTURES & DEVICES.

GENERAL DESCRIPTION

- 2'x4' FLOURESCENT LAMP FIXTURE
- 2'x2' FLOURESCENT LAMP FIXTURE
- 2'x4' OR 2'x2' FLOURESCENT FIXTURE ON EM CIRCUIT.
- SURFACE OR CEILING MOUNTED FLOURESCENT FIXTURE. (USE 1-1/2" SPACERS ON COMBUSTIBLE CEILING)
- FLOURESCENT FIXTURE SUSPENDED BELOW CEILING (MOUNT AT DESIGNATED HEIGHT ABOVE FLOOR)
- FLOURESCENT STRIP LIGHT WITH SEPARATE BALLAST (CONCEAL BALLAST IN ACCESSIBLE ENCLOSURE)
- SURFACE MOUNTED OR HID FIXTURE (NOTE WEIGHT LIMIT FOR BAR-JOIST HANGERS)
- INCANDESCENT OR HID FIXTURE RECESSED IN CEILING (KEEP J-BOX ACCESSIBLE FROM WITHIN FIXTURE)
- INCANDESCENT OR HID, WALL WASH RECESSED FIXTURE (AIM AS DIRECTED)
- INCANDESCENT OR HID FIXTURE WALL MOUNTED (CONFIRM HEIGHT OF OUTLET)
- INCANDESCENT CLUSTER OF ADJUSTABLE REFLECTOR LAMPS (AIM AS DIRECTED)
- FLOOD LIGHT
- BOLLARD
- LOW LEVEL EXIT SIGN +7" AFF.
- LIGHTED EXIT SIGN, CEILING, WALL MOUNTED OR RECESSED (ARROW SHOWS ROUTE TO LEGAL EXIT)
- LUMINAIRE ON POST TOP, SEE DETAIL (ANCHOR FIXTURE AGAINST DETAIL)
- DASHED SYMBOL IS EXISTING ITEM, OR FURNISHED BY OTHER (SEE SPECIFICATION FOR DIRECTIONS)
- STEP LIGHT
- JUNCTION BOX, WITH COVER (4" SQUARE, DEEP, WITH PLASTER RING)
- JUNCTION BOX, WALL MOUNTED, WITH COVER, +15" (CONFIRM LOCATION. SEE GEN. NOTE #9)
- JUNCTION BOX, FLUSH IN FLOOR, ADJUSTABLE HEIGHT COVER (SUBSCRIPTS: M=MIKE, P=PROJECTOR, C=CONTROLS)
- JUNCTION BOX, FLUSH IN FLOOR, ADJUSTABLE HEIGHT COVER (WITH 90 CLOSE ELBOW AND FLUSH FLOOR COUPLING)
- JUNCTION BOX, FOR DATA OUTLET.
- DUPLEX RECEPTACLE, FLUSH IN FLOOR, W.T. J-BOX (HINGED BRASS COVER: 20 AMP. 120 VOLT)
- DOUBLE DUPLEX RECEPTACLE, FLUSH IN FLOOR, W.T. J-BOX (HINGED BRASS COVER: 20 AMP. 120 VOLT)
- SINGLE OUTLET RECEPTACLE, RATING AND CONFIGURATION AS INDICATED ON PLAN. MOUNT AT +15" AFF
- DUPLEX RECEPTACLE, FLUSH IN WALL, GROUNDING TYPE +15" (20 AMP. 120 VOLT, COVER PLATE SPECIFIED)
- DOUBLE DUPLEX RECEPTACLE, FLUSH IN WALL (20 AMP. 120 VOLT)
- DUPLEX RECEPTACLE, MOUNTED AT CEILING, (FOR SHOW WINDOW CONNECTION 20A, 120V, 3W)
- DUPLEX RECEPTACLE, WITH GROUND FAULT CIRCUIT INTERRUPTER (20 AMP. 120 VOLT, 3W)
- SHADING DENOTES ONE-HALF RECEPTACLE SWITCHED +15" (MARK PLATE WITH ROUND RED DOT)
- SPECIAL PURPOSE RECEPTACLE, RATING AND CONFIGURATION AS INDICATED ON PLAN. MOUNT +15" AFF.
- POWER RECEPTACLE, IN SURFACE BOX, MTD. +15" (20A, 120V.)
- DUPLEX RECEPTACLE, WITH ISOLATED GROUND (20 AMP. 120 VOLT)
- MULTI-OUTLET ASSEMBLY
- FAN, CEILING OR WALL MOUNTED (SUPPORT FROM REINFORCED BRACKET PLATE)
- OUTLET FOR MOTOR; CONFIRM DIRECTION OF ROTATION (PROVIDE FLEXIBLE CONNECTION TO J-BOX FROM MOTOR)
- CIRCUIT BREAKER OF POLES, VOLTS, TRIP-AMPS NOTED (CONFIRM INTERRUPTING CAPACITY NEEDED)
- DUCT DETECTOR
- COMBINATION SMOKE/FIRE DAMPER
- SMOKE DETECTOR
- CONTROLLED RECEPTACLE

CONDUCTORS OF A MULTI-WIRE BRANCH CIRCUIT SHALL ORIGINATE FROM THE SAME PANELBOARD. THE BRANCH CIRCUIT SHALL BE PROVIDED WITH A MEANS THAT WILL SIMULTANEOUSLY DISCONNECT ALL UNGROUNDED CONDUCTORS AT THE POINT WHERE THE BRANCH CIRCUIT ORIGINATES.

ELECTRICAL SYMBOLS LIST

NOT ALL SYMBOLS APPLY TO THIS PROJECT; DISREGARD THOSE NOT USED ON PLANS AND IN DETAILS.

GENERAL DESCRIPTION

- BUZZER IN FLUSH BOX, CONFIRM HEIGHT
- BELL SURFACE OR RECESSED AS DESCRIBED (SUBSCRIPT DENOTES BELL DIAMETER INCHES)
- DATA/COMMUNICATION OUTLET FLUSH IN WALL +15" (PROVIDE 3/4" C.O. STUB UP +6" ABOVE CEILING)
- PUBLIC TELEPHONE OUTLET, FLUSH IN WALL +15" (PROVIDE 3/4" C.O. STUB UP +6" ABOVE CEILING)
- TELEPHONE OUTLET, PUBLIC/PRIVATE, FLUSH IN FLOOR (SEE SPECS. FOR SERVICE FITTINGS)
- JUNCTION BOX FLUSH ON WALL AT +6" AFF WITH WHIP FOR POWER CONNECTION TO FURNITURE SYSTEM.
- JUNCTION BOX FLUSH ON WALL AT +6" AFF FOR TEL/DATA CONNECTION TO FURNITURE SYSTEM. PROVIDE 1" C.O. STUB +6" ABOVE ACCESSIBLE CEILING.
- TERMINAL CABINET WITH HINGED DOOR, LOCK, BARRIERS (PROVIDE TERMINALS & 3/4" PLYWOOD BACKBOARD)
- TERMINAL BOARD OF 3/4" THICK PLYWOOD ON WALL (SIZE AS NOTED, PAINT TO MATCH WALL)
- TELEVISION CABLE OUTLET, FLUSH IN WALL +15" (SEE SPECS. FOR JACK & TERMINATING IMPEDANCE)
- CLOCK OUTLET, FLUSH IN WALL, CONFIRM HEIGHT (MASTER CONTROLLED 120 VOLT 60 CYCLE SYNCHRONOUS)
- PUSH-BUTTON FLUSH IN WALL, MOMENTARY CONTACT (ENGRAVE PLATE DESCRIBING PURPOSE)
- LOUDSPEAKER, CONE-TYPE, HOUSING, TRANSFORMER & GRILL ("V" DENOTES VOLUME CONTROL IN HOUSING)
- WALL TYPE DIMMER AND OCCUPANCY SENSOR
- FLOURESCENT LAMP DIMMER
- LOW VOLTAGE LAMP DIMMER
- VOLUME CONTROL L-PAD, FLUSH IN WALL, +42" (ENGRAVE PLATE)
- MICROPHONE OUTLET, 3-POLE, RECESSED, LOCKING TYPE (PROVIDE MATING PLUG)
- THERMOSTAT OUTLET, WALL MOUNTED, +48" (LOCATE SYMMETRICALLY WITH OTHER DEVICES)
- ELECTRIC HEATER, WALL MOUNTED, WITH DISCONNECT
- ELECTRIC HEATER IN EQUIPMENT PER SUBSCRIPT (C=C=CRANK CASE, A=D=AIR DUCT, W=W=WATER HTR)
- SWITCH, FLUSH IN WALL, TOGGLE, SINGLE-POLE S.T. +42" (SUBSCRIPT DENOTES UNIT CONTROLLED)
- SWITCH, FLUSH IN WALL, TOGGLE, TWO-POLE S.T. +42"
- SWITCH, FLUSH IN WALL, THREE WAY +42" (CONNECT TO MATCHING SWITCH FOR 3-WAY USE)
- SWITCH, FLUSH IN WALL, FOUR WAY +42" (CONNECT TO MATCHING SWITCHES FOR 3-4 WAY USE)
- SWITCH, FLUSH IN WALL, KEY OPERATED
- SWITCH, FLUSH IN WALL, MOMENTARY CONTACT, S.P.S.T.
- SWITCH, FLUSH IN WALL, WITH PILOT LIGHT (ENGRAVE PLATE WITH ITEM CONTROLLED)
- MOTOR STARTER, WITH THERMAL OVERLOADS (POLES, NOTED, HORSEPOWER RATED)
- VARIABLE SPEED CONTROL SWITCH
- MANUAL MOTOR-STARTER, MAGNETIC, THERMAL OVERLOADS, 3-P (PROVIDE AUXILIARY CONTACTS & CONTROL TRANSFORMER)
- STOP-START PUSH-BUTTON WITH PILOT LIGHT
- DISCONNECT SWITCH, MANUAL EXO. H.P. RATED ("F" MEANS FUSED TO AMPERE RATING MARKED)
- W.P. SIGN OUTLET ON FACE OF SOFFIT
- CEILING MOUNTED OCCUPANCY SENSOR
- WALL MOUNTED OCCUPANCY SENSOR WITH MANUAL ON/OFF CAPABILITY

COMMUNICATION & ALARM

- PUSHBUTTON MOMENTARY CONTACT +48"
- "ON-OFF" PUSH BUTTON MOMENTARY CONTACT +48"
- BUZZER, +7"-6" UNLESS OTHERWISE NOTED
- GONG, +7"-6" UNLESS OTHERWISE NOTED
- OUTDOOR SPEAKER, PROVIDE 1/2"C.O. WITH PULL STRING TO TELEPHONE CLOSET.
- RADIO ALARM GONG, +7"-6" UNLESS OTHERWISE NOTED PROVIDE 1/2"C.O. WITH PULL STRING TO TELEPHONE CLOSET.
- CEILING MOUNTED SPEAKER (VOL DENOTES VOLUME CONTROL) PROVIDE 1/2"C.O. WITH PULL STRING TO TELEPHONE CLOSET.
- SMOKE DETECTOR
- KEY PAD
- SCU PRINTER (PROVIDED BY FIRE DEPARTMENT)
- FIRE ALARM FULL STATION
- FIRE ALARM STROBE/HORN
- FIRE ALARM HORN
- FIRE ALARM LIGHT HORN
- SPRINKLER BELL
- DOOR BUZZER
- DOOR BELL ANNOUNCER
- FIRE ALARM CONTROL PANEL

NOTE: ALL MOUNTING HEIGHTS ARE TO CENTER-LINE UNLESS OTHERWISE NOTED

MOUNTING HEIGHTS IN SYMBOL LIST APPLY UNLESS OTHERWISE NOTED ON DRAWINGS.

GENERAL DESCRIPTION

- DISCONNECT DEVICE, LOAD-BREAK, NON-AUTOMATIC (LABEL AS MANUAL SWITCH ONLY)
- DISCONNECT SWITCH & FUSE, DIAGRAMMATIC
- SOLENOID VALVE IN PIPELINE (CONFIRM COIL VOLTAGE & LOCATION)
- EXISTING TO REMAIN
- EXISTING TO BE REMOVE
- CONDUIT STUB-UP WITH COUPLING FLUSH IN FLOOR (TO PERMIT FUTURE REMOVAL)
- CONDUIT RUN EXPOSED, ALIGN WITH STRUCTURE (ATTACH TO SUPPORTS NOT TO EXCEED 5FT. APART)
- CONDUIT CONCEALED IN OR UNDER FLOOR; OR UNDERGROUND (CONFIRM DEPTH; GRADE TO DRAIN INTO PULL BOXES)
- 1/2" CONDUIT WITH 2#12 WIRES
- 1/2" CONDUIT WITH 3#12 WIRES
- 1/2" CONDUIT WITH 4#12 WIRES
- 1/2" CONDUIT WITH 5#12 WIRES
- 3/4" CONDUIT WITH 6#12 WIRES
- NUMBER INDICATES GAUGE OF WIRE IN CODE SIZED CONDUIT.
- CONDUIT-ONLY WITH #12 TW COPPER PULL-WIRE (3/4" MINIMUM SIZE, UNLESS NOTED OTHERWISE)
- HOMERUN TO CIRCUITS #1 & #3 IN PANEL "A" (CROSSMARKS INDICATE NUMBER OF WIRES)
- CONDUIT DROPPING DOWN FROM RUN (IF CONDUIT IS USED KEEP COVER ACCESSIBLE)
- CONDUIT RISING UP FROM RUN (IF CONDUIT IS USED, KEEP COVER ACCESSIBLE)
- GROUND CONNECTION WITH ACCESSIBLE CLAMP (TO COLD WATER PIPE OR DRIVEN GROUND ROD)
- UFER GROUND
- PULL BOX WITH SCREW HELD METAL COVER PLATE (DIMENSIONS CODE-SIZED UNLESS NOTED)
- BRANCH PANELBOARD, WALL MOUNTED, SEE SCHEDULE
- DISTRIBUTION SUB-SWITCHBOARD, SEE SCHEDULE
- MAIN SWITCHBOARD, POWER OR LIGHT, FLOOR STANDING, ENCL. (SEE ONE LINE DIAGRAM & LOAD SUMMARY)
- PULL SECTION FOR UNDERGROUND SERVICE TO SWITCHBOARD (PROVIDE PERFORATED SCREW HEADS FOR UTILITY SEAL)
- CONTROL PANEL WITH DEVICES SHOWN OR DESCRIBED (MOUNT DEVICES INDEPENDENT FROM HINGED COVER)
- 3/4"C.O. FOR TELEPHONE SYSTEM.
- 3/4" C.O. FOR DATA OUTLET
- CONDUIT FOR FIRE ALARM SYSTEM
- UNDER FLOOR DUCT WITH OUTLETS, ACCESSORIES & J-BOX
- NUMBERED NOTE FOR ALL ELECTRICAL DRAWINGS
- DETAIL DESIGNATION FOR ITEM & DRAWING NUMBER

ABBREVIATIONS

- | | | | |
|-------|--|---------|---|
| A | AMPERE | (N) | NEW |
| AH | AMPERE-HOUR | N.I.C. | NOT IN CONTRACT |
| AFF | ABOVE FINISHED FLOOR | NEC | NATIONAL ELECTRICAL CODE |
| AFG | ABOVE FINISHED GRADE | NL | NIGHT LIGHT |
| CKT | CIRCUIT | NTS | NOT TO SCALE |
| C.O. | CONDUIT ONLY | P | POLE, PHASE |
| DP | DISTRIBUTION PANEL | PNL | PANEL BOARD |
| (E) | EXISTING | PEC | PHOTO ELECTRIC CELL |
| EF | EXHAUST FAN | R | REMOVE |
| ELR | END OF LINE RESISTOR | SA | SATIN ALUMINUM |
| EOL | END OF LINE | SC | SHORT CIRCUIT |
| EM | EMERGENCY | SSS | SATIN STAINLESS STEEL |
| FA | FIRE ALARM | TEL | TELEPHONE |
| FC | FOOT CANDLE | TL | TWIST-LOCK CONSTRUCTION |
| FCO | FULL CUT OFF | TSC | TIME SWITCH CONTROL |
| FLUOR | FLOURESCENT | TSP | TWISTED SHIELDED PAIR |
| GFP | GROUND FAULT PROTECTION | TYP | TYPICAL |
| GND | GROUND | U.O.N. | UNLESS OTHERWISE NOTED |
| HOA | "HAND OFF AUTOMATIC" | V | VOLTS |
| HP | HORSEPOWER RATING | VD | VOLTAGE DROP |
| INC | INCANDESCENT | W/ | WITH |
| J-BOX | JUNCTION BOX | W.M. | WIREMOLD |
| KA | KILO AMPERES. | WP | WEATHERPROOF CONSTRUCTION |
| KVA | KILO-VOLT AMPS | WT | WEATHER TIGHT CONSTRUCTION |
| KW | KILOWATT | WBE | WHITE BAKED ENAMEL |
| LCL | "LONG CONTINUOUS LOAD" | WPE | WHITE PORCELAIN ENAMEL |
| LM | LARGEST MOTOR | XFMR | TRANSFORMER |
| L.O. | LUGS ONLY | (XR) | EXISTING TO BE REMOVED |
| LTG | LIGHTING | (+)'-Y" | MOUNTING HEIGHT (TO CENTER OF DEVICE) |
| LV | LOW VOLTAGE | 5SD | METAL BOX 4-11/16" SQUARE (X) 2-1/8" DEEP |
| MC | MOMENTARY CONTACT ACTION | | |
| MCA | MINIMUM CIRCUIT AMPACITY | | |
| MH | METAL HALIDE | | |
| MHT | MOUNTING HEIGHT (TO BOTTOM OF FIXTURE) | | |
| MOCP | MAXIMUM OVER CURRENT PROTECTION | | |

E ENGINEERS

CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW
2	08.31.21	ISSUED FOR PLAN CHECK

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED


SHEET SIZE: 24x36

DRAWING TITLE:


SYMBOLS &
GENERAL NOTES

SHEET NO:

E200



CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:

LIGHT FIXTURE SCHEDULE

SHEET NO:

E201

LIGHTING LUMINAIRE SCHEDULE

TYPE (Watts)	TYPICAL LOCATION	MOUNTING METHOD	MANUFACTURER and CATALOG NUMBER	LAMPS	DESCRIPTION
A (15.9)	DORMS	RECESSED	LITHONIA LIGHTING #2VTL2-20L-ADP-EZ1-LP830-N100 <u>ACCESSORIES:</u> #XX-XX PER ARCHITECT OR CONTRACTOR	(1) 2000 LUMENS LED 80CRI 3000°K 120V	2' BY 2' VOLUMETRIC TROFFER WITH ACRYLIC LINEAR PRISMATIC DIFFUSER AND LED DIMMING DRIVER.
A1 (33.1)	DAY ROOM	RECESSED	LITHONIA LIGHTING #2VTL2-40L-ADP-EZ1-LP830-N100 <u>ACCESSORIES:</u> #XX-XX PER ARCHITECT OR CONTRACTOR	(1) 4000 LUMENS LED 80CRI 3000°K 120V	2' BY 2' VOLUMETRIC TROFFER WITH ACRYLIC LINEAR PRISMATIC DIFFUSER AND LED DIMMING DRIVER.
A2 (33.1)	LAUNDRY	RECESSED	LITHONIA LIGHTING #2VTL2-40L-ADP-EZ1-LP830-N100 <u>ACCESSORIES:</u> #DGA22-FS/VT	(1) 4000 LUMENS LED 80CRI 3000°K 120V	2' BY 2' VOLUMETRIC TROFFER WITH ACRYLIC LINEAR PRISMATIC DIFFUSER AND LED DIMMING DRIVER. EQUIPPED WITH DRYWALL CEILING ADAPTER WITH TRIM KIT.
B (19.6)	HALLWAY, RESTROOM AND STUDY	RECESSED	PINNACLE ARCHITECTURAL LIGHTING EDGE 2" RECESSED #EV2D-A-830-4-FL(F)-U-EE1-1-0-GR	(1) LED 2,000 LUMENS 80CRI 3000°K 120V	4' LINEAR BY 2" WIDE LUMINAIRE WITH SATIN SHIELDING LENS AND 1/2" FLANGE MOUNTING HARDWARE AND LED DIMMABLE DRIVER. FINISH TO BE GRAPHITE. FIXTURE OPTIONS PER CONTRACTOR.
B1 (20.4)	ORIGINAL RESTROOMS AND HALLWAY	SURFACE	PINNACLE ARCHITECTURAL LIGHTING EDGE 2" SURFACE #EX2D-A-N-830-4-S-U-EE1-1-0-GR	(1) LED 2,000 LUMENS 80CRI 3000°K 120V	4' LINEAR BY 2" WIDE LUMINAIRE WITH SATIN SHIELDING LENS AND LED DIMMABLE DRIVER. FINISH TO BE GRAPHITE. FIXTURE OPTIONS PER CONTRACTOR.

LIGHTING LUMINAIRE REFERENCE NOTES:

- CONFIRM FIXTURE PART NUMBERS DENOTED BY "XX" WITH ARCHITECT PRIOR TO ORDER. EXAMPLES OF PART NUMBERS INCLUDE TRIM COLOR, FINISH, OPTIONS AND LAMP COLOR TEMPERATURE.
- CERTAIN FIXTURES DESIGNATED BY 'em' ON THE FLOOR PLANS SHALL CONTAIN AN INTEGRAL 90 MINUTE EMERGENCY LIGHTING BALLAST. THE EMERGENCY EXIT ILLUMINATION SHALL BE SUPPLIED FROM STORAGE BATTERIES. SEE CIRCUITING SHOWN ON LIGHTING PLANS FOR THE WIRING REQUIREMENTS. SEE LUMINAIRE SCHEDULE ABOVE AND DETERMINE BALLAST REQUIREMENTS.
- INCLUDE IN BASE BID ALL LABOR AND MATERIALS REQUIRED FOR A COMPLETE INSTALLATION OF ALL LUMINAIRES INDICATED ON THE DRAWINGS.
- ELECTRICAL CONTRACTOR TO COORDINATE MOUNTING HEIGHT OF ALL LIGHT LUMINAIRES WITH ARCHITECTURAL, INTERIOR DESIGN AND LIGHTING CONSULTANT DESIGN DRAWINGS IN ADDITION TO OTHER TRADES PRIOR TO ROUGH-IN.
- REFER TO ARCHITECTURAL CEILING PLANS FOR EXACT LOCATION OF ALL LIGHT LUMINAIRES.
- PROVIDE AND INSTALL ALL NECESSARY SUPPORTS INDEPENDENT OF THE CEILING SYSTEM AS REQUIRED PER CODES AND LOCAL ORDINANCES.
- CONTRACTOR IS RESPONSIBLE TO VERIFY TYPE OF CONSTRUCTION AT EACH LUMINAIRE LOCATION AND PROVIDE THE REQUIRED TRIMS AND MOUNTING ACCESSORIES OR KITS FOR THE APPLICATION.
- DOWNLIGHTS RATED FOR TC MUST BE 3" AWAY FROM ANY INSULATION. CONFIRM ARCHITECTURAL DETAILS PRIOR TO ORDER.
- MANUFACTURER TO PROVIDE ALL STRIP LIGHT FIXTURES WITH DISCONNECTING MEANS INSIDE OR OUTSIDE THE LUMINAIRE THAT CAN DISCONNECT ALL CONDUCTORS WIRED TO THE BALLAST.
- CONTRACTOR TO CONFIRM FIRE-RATING OF CEILING MOUNTED LUMINAIRES WITH ARCHITECT PRIOR TO BID. LUMINAIRES IN CEILINGS WITH 2-HOUR FIRE RATING SHALL BE EQUIPPED WITH RED 2-HOUR BOXES.
- RECESSED LUMINAIRES IN FIRE RATED CEILINGS AND AIR PLENUMS SHALL BE APPROVED FOR THE FIRE RATINGS OF THE CEILING OR SHALL BE FULLY ENCLOSED IN A FIRE-RATED HOUSING OR STRUCTURE ACCEPTABLE TO THE AUTHORITY HAVING JURISDICTION.
- VERIFY EXIT SIGN LOCATIONS AND DIRECTIONAL ARROWS WITH ARCHITECT'S FINAL EGRESS PLAN DRAWING AND THE AUTHORITY HAVING JURISDICTION PRIOR TO ORDERING EQUIPMENT. PROVIDE SEPARATE NEUTRAL CONDUCTORS TO ALL LINE VOLTAGE DIMMED CIRCUIT SWITCH LEG. DO NOT SHARE NEUTRAL CONDUCTORS IN LINE VOLTAGE DIMMED CIRCUITS. **BUILDING CODE DOES NOT REQUIRE EXIT SIGNS FOR THIS PROJECT.**

C (9.0)	KITCHEN AND STUDY	SURFACE	PINNACLE ARCHITECTURAL LIGHTING FINA F14D #F14D-A-830LO-S-U-EE1-1-0-GR	(1) LED 838 LUMENS 80CRI 3000°K 120V	14" DIAMETER WITH FLUSH SATIN SHIELDING LENS AND LED DIMMABLE DRIVER. FINISH TO BE GRAPHITE. FIXTURE OPTIONS PER CONTRACTOR.
D (8)	DORM BEDS	SURFACE	LIGMAN LIGHTING USA LEEDS 1 SMALL #ULEW-30001-8WLED-T4-W30-02-120/277V <u>OPTIONS:</u> #XX-XX	(1) LED 795 LUMENS >80 CRI 3000°K 120V	8" HIGH AND 4" WIDE DECORATIVE SURFACE WEDGE DOWNLIGHT WITH TYPE IV BEAM DISTRIBUTION IN DARK GREY FINISH. FIXTURE OPTIONS PER CONTRACTOR. ARCHITECT SHALL CONFIRM COLOR TEMPERATURE.
E (10.4)	KITCHEN AND HALLWAY	RECESSED	LITHONIA LIGHTING LDN6 #LDN6-30/-10-LO6-BR-LD-MVOLT-EZ10	(1) LED 1000 LUMENS 80 CRI 3000°K 120V	6" DIAMETER OPEN DOWNLIGHT WITH BLACK TRIM COLOR AND MATTE DIFFUSE FINISH. EQUIPPED WITH AN ELECTRONIC LED DIMMING DRIVER. FIXTURE OPTIONS PER CONTRACTOR.
F (20.0)	RESTROOMS	SURFACE	PURE EDGE LIGHTING TWIGGY T1 VANITY WALL #TW2-T1-4SQ-48IN-30K-BK	(1) LED 306 LUMENS/FT 95+CRI 3000°K 120V TO 24VDC	48" LINEAR VANITY WITH ELECTRONIC LOW VOLTAGE POWER SUPPLY FURNISHED IN JUNCTION BOX. LENS IS TUBULAR AND COMES WITH A 4" FLOATING SQUARE CONOPY IN SATIN BLACK FINISH.
G (18.0)	KITCHEN AND LAUNDRY	SURFACE	BRUCK LIGHTING SERIES wUndercab CCT SELECT #138546-32-3CCT-3000K-90CRI-120-WH <u>ACCESSORIES:</u> #XX-XX PER CONTRACTOR	(1) LED 1350 LUMENS >90CRI 3000°K 120V	32-3/8" LINKABLE LINEAR UNDERCABINET LIGHT WITH LED DRIVER. FINISH IN WHITE. ALL ACCESSORIES PER ELECTRICAL CONTRACTOR.

13. TEST FOR ILLUMINATION AND EXIT SIGNS, INCLUDING DIRECTIONAL EXIT SIGNS POWER BY EITHER THE NORMAL PREMISES WIRING OR ANY ADDITIONALLY REQUIRED EMERGENCY SYSTEMS SHALL BE CONDUCTED IN THE PRESENCE OF THE BUILDING INSPECTION STAFF TO ENSURE COMPLIANCE. THE TEST TIMES FOR EMERGENCY SYSTEMS SHALL BE ARRANGED IN ADVANCE AND ALL STAFFING COST ASSOCIATED WITH EITHER PRE-HOURS OR AFTER-HOURS SHALL BE PAID AT THIS TIME. THE TESTING AND APPROVAL OF SUCH SYSTEMS SHALL OCCUR PRIOR TO THE ISSUANCE OF A TEMPORARY CERTIFICATE OF APPROVAL OF THE PROJECT. **BUILDING CODE DOES NOT REQUIRE EXIT SIGNS FOR THIS PROJECT.**

APPROVED:


DATE: _____ APPROVED BY: _____

BUILDING CODE DOES NOT REQUIRE EXIT SIGNS FOR THIS PROJECT.

H (16.0)	SHOWER	RECESSED	CON-TECH LIGHTING LED RECESSED DOWNLIGHT 1000 SERIES #RA4LNC-130K-12D2 <u>OPTIONS:</u> #XX-XX <u>TRIM:</u> #CTR4327L-CLR-PL	(1) LED 120V 3000°K	4" DIAMETER DOWNLIGHT WITH LED DRIVER LISTED FOR WET APPLICATION. TRIM IS RECESSED TWO PIECE PER ARCHITECT. FIXTURE OPTIONS PER CONTRACTOR.
I (14.0)	EXTERIOR	SURFACE	LIGMAN LIGHTING USA LEEDS 2 MEDIUM #ULEW-30011-14WLED-T3-W35-02-120/277V <u>OPTIONS:</u> #XX-XX	(1) LED 1660 LUMENS >80 CRI 3000°K 120V	8" HIGH DECORATIVE SURFACE WEDGE DOWNLIGHT WITH TYPE III BEAM DISTRIBUTION IN DARK GREY FINISH. FIXTURE OPTIONS PER CONTRACTOR. ARCHITECT SHALL CONFIRM COLOR TEMPERATURE.
J (10.4)	ALARM LIGHTS	RECESSED	LITHONIA LIGHTING LDN6 #LDN6-30/-10-LO6-BR-LD-MVOLT-EZ10	(1) LED 1000 LUMENS 80 CRI 3000°K 120V	6" DIAMETER OPEN DOWNLIGHT WITH CLEAR TRIM COLOR AND MATTE DIFFUSE FINISH. EQUIPPED WITH AN ELECTRONIC LED DIMMING DRIVER. FIXTURE OPTIONS PER CONTRACTOR.
K (10.4)	EXTERIOR	RECESSED	LITHONIA LIGHTING LDN6 #LDN6-35/-10-LO6-BR-LD-MVOLT-EZ10	(1) LED 1000 LUMENS 80 CRI 3500°K 120V	6" DIAMETER OPEN DOWNLIGHT WITH BLACK TRIM COLOR AND MATTE DIFFUSE FINISH. EQUIPPED WITH AN ELECTRONIC LED DIMMING DRIVER. FIXTURE OPTIONS PER CONTRACTOR.

FAULT CURRENT CALCULATION

AVAILABLE FAULT CURRENT FROM UTILITY = 42,000A @ 240V-1PH
 MOTOR CONTRIBUTION ESTIMATE = 750A
FINAL MAXIMUM AVAILABLE FAULT CURRENT IS 42,750A @ 240V - 1PH



1 NEW SINGLE LINE DIAGRAM
 Scale : NTS

SINGLE LINE DIAGRAM REFERENCE NOTES:

- THE MAXIMUM AVAILABLE FAULT CURRENT CONTRIBUTION FROM THE UTILITY AT THE NEW SERVICE IS 42,750A AT 240V-1PH, PER SCE AND CALCULATION. (SEE SHEET E600)
- ALL SERVICE EQUIPMENT SHALL BE LEGIBLY MARKED WITH THE MAXIMUM AVAILABLE FAULT CURRENT. INCLUDE THE DATE FOR WHEN THE CALCULATIONS WERE PERFORMED. NAMEPLATES SHALL BE WEATHERPROOF AND WEATHER RESISTANT.
- THE NEW MAIN SERVICE SWITCHBOARD, PULL SECTION AND FEEDER BREAKERS AND BRANCH CIRCUIT BREAKERS SHALL BE FULLY RATED FOR A MAXIMUM SHORT CIRCUIT RATING OF 65,000 AMPS OF SYMMETRICAL FAULT CURRENT AT 240V-1φ.
- PROVIDE A NEW FEEDER AS INDICATED AND MAKE LINE VOLTAGE CONNECTIONS TO THE NEW PANELBOARD "C" AND EXISTING PANELBOARD "NP" VIA EXISTING TRANSFER SWITCHES FOR BACK-FEED OF EXISTING SERVICES. ALL NEW LINE VOLTAGE CONNECTIONS TO MEET MANUFACTURER AND UL LISTINGS.
- THE EXISTING SINGLE PHASE SERVICE TENANT PANELS "B" AND "E" ARE TO REMAIN. INTERCEPT ALL EXISTING BRANCH CIRCUIT CONDUIT AND WIRE THAT REMAIN AND EXTEND TO BRANCH CIRCUIT BREAKERS LOCATED IN THE NEW 1-PHASE 3-WIRE DISTRIBUTION SYSTEM OR EXISTING PANELS. AS BUILT PANEL SCHEDULES ACCORDINGLY UPON COMPLETION OF CONSTRUCTION AND REPORT FINDINGS TO ENGINEER OF RECORD.
- THE EXISTING SERVICE SWITCHBOARD TO BE DEMOLISHED FOR SERVICES "MS". INTERCEPT EXISTING FEEDER CONDUIT AND INSTALL ALL NEW FEEDER WIRING FROM NEW DISTRIBUTION PANEL "DPA" TO PANELS "C" AND "NP". CONTRACTOR TO COORDINATE MEANS AND METHODS OF FLATTENING THE METER COMPARTMENT OR REMOVING IT ENTIRELY. METHOD SHALL MEET SCE AND BUILDING AND SAFETY DEPARTMENT REQUIREMENTS.
- CONTRACTOR SHALL CONTACT UTILITY COMPANY TO REMOVE EXISTING UNDERGROUND SERVICE CONDUCTORS, DISCONNECT THE EXISTING UTILITY METERING AND MAKE CONNECTION TO NEW SERVICE.
- 3/4" C, 1 #1/0 CU GROUND. GROUNDING ELECTRODE SYSTEM SHALL COMPLY WITH NEC ARTICLE 250-52 AND INCLUDE ALL AVAILABLE METHODS.
- BONDING SHALL BE PROVIDED AT METAL PIPING SYSTEM(S) (INCLUDING GAS PIPING) TO ENSURE ELECTRICAL CONTINUITY. SEE NEC ARTICLE 250-104 FOR MEANS AND METHODS. THE POINT OF ATTACHMENT OF ALL CONDUIT JUMPERS SHALL BE ACCESSIBLE. ALL COLD WATER AND NATURAL GAS PIPING TO BE BONDED WITHIN 5' OF ENTRY INTO BUILDING.
- LENGTH OF FEEDERS AND BRANCH CIRCUITS ARE FOR ENGINEERING CALCULATIONS ONLY AND SHALL NOT BE USED FOR BIDDING OR CONSTRUCTION PURPOSES.
- EACH ELECTRICAL SERVICE SHALL HAVE PERMANENTLY INSTALLED USER ACCESSIBLE METERING OF TOTAL ELECTRICAL ENERGY THAT INCLUDES:
 - INSTANTANEOUS KW DEMAND
 - HISTORICAL PEAK DEMAND (KW)
 - RESETTABLE KWH.
- PANELBOARD AND BRANCH CIRCUIT BREAKERS TO BE FULLY RATED FOR A MINIMUM OF 42,000A OF SYMMETRICAL FAULT CURRENT AT 120/240V, 1-PHASE.
- PANELBOARD AND BRANCH CIRCUIT BREAKERS TO BE FULLY RATED FOR A MINIMUM OF 22,000A OF SYMMETRICAL FAULT CURRENT AT 120/240V, 1-PHASE.
- SERVICE EQUIPMENT, SWITCHBOARD AND PANELBOARDS ARE DESIGNED ON "EATON CUTLER -HAMMER" EQUIPMENT. USE OF APPROVED EQUAL EQUIPMENT REQUIRING DIMENSIONS OTHER THAN SHOWN ON THE PLANS SHALL BE APPROVED BY THE ENGINEER OF RECORD PRIOR TO ORDER.
- 2" C., (3) #4/0 CU THWN AND (1) #4 CU GROUND.
- 1-1/2" C., (3) #1/0 CU THWN AND (1) #6 CU GROUND.
- 2" C., (3) #2/0 CU THWN AND (1) #6 CU GROUND.
- SEE DISTRIBUTION PANEL "DPA" PANEL SCHEDULE ON SHEET E500 FOR REQUIRED SPARE CIRCUIT BREAKERS AND SPACES FOR FUTURE FEEDER AND BRANCH CIRCUIT BREAKERS. SINGLE LINE DIAGRAM VERSION DOES NOT DIAGRAMMATICALLY REPRESENT ALL REQUIREMENTS.
- THE EXISTING SINGLE LINE DIAGRAM HAS BEEN PROVIDED BY THE FIRE STATION AND OBSERVED TO REFLECT ALL THE EQUIPMENT THAT IS CURRENTLY INSTALLED AND ENERGIZED IN THE EXISTING FIELD CONDITIONS. IT SHALL BE THE ELECTRICAL CONTRACTOR'S RESPONSIBILITY TO FIELD VERIFY THE POWER SYSTEM ON THE BLUE PRINT MATCHES EXISTING CONDITIONS AND REPORT ANY NEW FINDINGS TO THE ENGINEER OF RECORD PRIOR TO ORDERING ANY NEW EQUIPMENT. FINDINGS THAT ARE OTHER THAN DRAWN MAY IMPACT THE NEW SERVICE DESIGN.

SINGLE LINE CALCULATION TABLE


5205 CALLE MAYOR
 TORRANCE, CA

MAIN SERVICE "MSA": 120/240V-1 PHASE-3 WIRES

PANEL TAG	FEEDER LENGTH (LF)	VOLTAGE DROP (%)	AVAILABLE FAULT CURRENT (AMPS)	COMMENTS
MSA			42,750	NEW AND FULLY RATED FOR 65,000 AIC. FAULT CURRENT TOTAL INCLUDES ADDITIONAL ESTIMATED 750A OF CURRENT DUE TO MOTOR CONTRIBUTION FROM MECHANICAL SYSTEMS.
DP	0		42,750	NEW AND FULLY RATED FOR 65,000 AIC.
C	30'	FEEDER = 0.30% TOTAL < 5.00%	26,739	NEW AND FULLY RATED FOR 65,000 AIC.
NP	15'	FEEDER = 0.14%	31,566	EXISTING AND FULLY RATED FOR 65,000 AIC.
A	80' (95' TOTAL)	FEEDER SEG = 0.79% FEEDER = 0.93% TOTAL < 5.00%	10,676	NEW AND FULLY RATED FOR 22,000 AIC.

GENERAL NOTES:

- LENGTHS OF FEEDERS AND BRANCH CIRCUITS ARE FOR ENGINEERING CALCULATIONS ONLY AND SHALL NOT BE USED FOR BIDDING OR CONSTRUCTION PURPOSES.



BDLG. OWNER:

PROJECT:
FIRE STATION 4 RENOVATION

PROJECT ADDRESS:
 5205 CALLE MAYOR
 TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:
NEW SINGLE LINE DIAGRAM & DETAILS

SHEET NO: **E300**



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to this office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:

MAIN SERVICE ELEVATION & DETAILS

SHEET NO:

E302



EXISTING PORTABLE GENSET CONNECTION PANEL
225A-1PH-3W
- IN A NEMA '3R' ENCLOSURE
- WITH HINGED COVER
FIELD VERIFY IT HAS BEEN INSTALLED, APPEARS TO BE MISSING FROM SITE OBSERVATION #1.

EXISTING MANUAL TRANSFER SWITCH 'TS-1M'
- IN A NEMA '3R' ENCLOSURE.
- EATON CUTLER HAMMER.
- SHORT CIRCUIT RATING: 100,000 AIC.
- FIELD VERIFY RATING IS 225A-3PH UP TO 600V; REPORT TO ENGINEER OF RECORD.
- **TO REMAIN.**

EXISTING PANEL 'NP'
- **TO REMAIN.**

EXISTING AUTO TRANSFER SWITCH 'TS-2'
- IN A NEMA '3R' ENCLOSURE.
- WITH TEST SWITCH.
- GENERAC GENERATOR CONTROL BOX.
- SHORT CIRCUIT RATING: xx,000 AIC.
- FIELD VERIFY RATING MEETS 225A OF LOAD.
- **TO REMAIN.**

EXISTING 200A EXO 'EXO-1'
- IN A NEMA '3R' ENCLOSURE
- CONTRACTOR TO VERIFY SPECS MATCHES SHEET E301.
- **TO REMAIN.**


PROPOSED LOCATION OF NEW METERED MAIN SERVICE SWITCHBOARD 'MSA'
400A @ 120/240V-1PH-3W
- IN A STAND-UP NEMA '3R' ENCLOSURE.
- CONTRACTOR SHALL RELOCATE HOSE BIB AND HOSE HOLDER.

3 EXISTING ELECTRICAL AREA AND PROPOSED NEW MAIN SERVICE "MSA" LOCATION
SCALE: NOT TO SCALE



EXISTING UTILITY POLE #xxx-xxx
EQUIPPED WITH 1 BUCKET STYLE TRANSFORMER
FEEDS 'MS' VIA UNDERGROUND CONDUIT
- TO BE VERIFIED BY SCE SERVICE PLANNER.
- CONFIRM DIAMETER OF UNDERGROUND DUCT BANK
- **TO REMAIN AND SERVICE TO BE REDESIGNED.**

2 EXISTING UTILITY POLE LOCATION
SCALE: NOT TO SCALE



NEW EATON CUTLER HAMMER SWITCHGEAR SERIES "PRL-C" OR APPROVED EQUAL. IN A NEMA 3R ENCLOSURE.

SWITCHGEAR SHALL BE LOCATED ON A HOUSE-KEEPING PAD PER SCE SPECIFICATIONS. SEE SHEET E600 FOR DETAILS.

1 NEW MAIN SERVICE "MSA" ELEVATION
SCALE: NOT TO SCALE



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.xx.21	ISSUED FOR PLAN CHECK

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED


SHEET SIZE: 24X36

DRAWING TITLE:


**GROUND ELECTRODE
CONDUCTING SYSTEM**

SHEET NO:

E303




1
E303 **GROUNDING ELECTRODE SYSTEM**
SCALE: NOT TO SCALE



2
E303 **GROUND ROD AND CONCRETE BOX**
SCALE: NOT TO SCALE

CONTRACTOR SHALL PROVIDE A CERTIFIED TEST SHOWING THAT THE RESISTANCE TO GROUND IS 25 OHMS OR LESS FOR SINGLE GROUND ROD. OR, INSTALL TWO GROUND RODS NOT LESS THAN 6'-0" APART [NEC 253(A)]

* PROVIDE CONCRETE ENCLOSURE AS SHOWN IN DETAIL #2, THIS SHEET.



CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:
SINGLE LINE CALCULATIONS
AND DETAILS

SHEET NO:

E304

PROJECTED LOAD CALCULATION FOR EXISTING SERVICE 'MS'

120/240V 1PH-3W CALCULATION PER NEC ARTICLE 220
5205 CALLE MAYOR, TORRANCE

EXISTING SCE METER FOR THE FIRE STATION SERVICE: SCE #223000-009046 MAXIMUM DEMAND FOR THE PAST 12 MONTHS IS 20 KW BASED ON SCE UTILITY BILL DATED 2/3/2021	20 KW	
CONVERT TO KVA (ASSUME 80% POWER FACTOR)	25 KVA	
CONVERT TO AMPS	104 A	
25% CODE REQUIRED MULTIPLIER	26 A	
SUB-TOTAL DEMAND LOAD	130 A	
EXISTING BASELINE PRIOR TO CAPITAL BUDGET PROJECT = (CONVERT TO VA)	130A	31,200 VA
EXISTING CONNECTED LOAD BEING DEMOLISHED		
LIGHTING – (18) 4 FOOT TROFFER WITH 2 LAMP FLUORESCENTS		-1,260 VA
LIGHTING – (2) DOWNLIGHTS WITH QUAD PL LAMPS		-70 VA
CONVENIENCE OUTLETS – (8) LOCATIONS		-1,440 VA
LCL		-333 VA
SUB-TOTAL		-3,103 VA

Page 1 of 2

EXISTING CONNECTED LOAD BEING REPLACED WITH NEW CONNECTED LOAD OF LIKE TYPE		
GARBAGE DISPOSER, (2) REFRIGERATORS, COFFEE POT		0 VA
MICROWAVE OVEN (COUNTER TOP), DISHWASHER		0 VA
WASHING MACHINE (LAUNDRY AND CIRCUITED TO PANEL 'B') [F.V.]		0 VA
SUB-TOTAL (BEST CASE SCENARIO FOR SERVICE UPGRADE EVALUATION ONLY)		0 VA
NEW CONNECTED LOAD BEING ADDED TO EXISTING SERVICE 'MS'		
PANEL 'A' (RECEPTACLE AND LIGHTING LOADS)		6,168 VA
MECHANICAL SYSTEMS – NEW SPLIT UNIT CIRCUITED TO NEW PANEL 'C' INCLUDING LARGEST MOTOR		3,600 VA
NEW ROOF OUTLET REQUIRED BY CODE		180 VA
PLUMBING SYSTEM – GAS WATER HEATING BEING IMPLEMENTED		0 VA
SUB-TOTAL		9,948 VA
TOTAL CALCULATED DEMAND LOAD		
		38,045 VA
CONVERT TO AMPERES	159.0 A	
ADDITIONAL ALLOWED LOAD NOT TO EXCEED	< 0.5 A	120 VA

**PER THE CALCULATION ABOVE, THE EXISTING 200A-1PH SERVICE CAN NOT BE REUSED. A
SERVICE UPGRADE TO 400A AT 120/240V-1PH IS REQUIRED FOR THE BUILDING.**


Demand Load information completed the week of May 24, 2021. This calculation is for design development purposes only and shall not be updated through project completion. See panel schedules and the new single line diagram for final connected load analysis.

Page 2 of 2

SEE SHEET A2.1 FOR THE SCOPE OF THE DEMOLITION WORK

GENERAL NOTES FOR DEMOLITION:



- DEMOLITION WORK SHALL BE PERFORMED ACCORDING TO THE ARCHITECTURAL AND ELECTRICAL CONSTRUCTION DOCUMENTS.
- THE ELECTRICAL CONTRACTOR SHALL REMOVE ALL LIGHT LUMINAIRES AND ELECTRICAL DEVICES WITH ASSOCIATED CONDUIT AND WIRING IN THE WAY OF THE NEW TENANT IMPROVEMENT SCOPE OF WORK. REMOVE, REROUTE AND REWIRE EXISTING FIXTURES, RECEPTACLES AND JUNCTION BOXES THAT REMAIN.
- EXTENDED BRANCH CIRCUIT CONDUIT AND WIRING TO MATCH EXISTING FOR ALL RELOCATED DEVICES AND EQUIPMENT.
- MAINTAIN CIRCUIT CONTINUITY TO ALL EXISTING EQUIPMENT AND DEVICES THAT REMAIN IN OPERATION. RE-ROUTE CONDUIT AND WIRING FROM THE DEVICES THAT ARE REMOVED TO THE NEAREST DEVICE WHICH WILL REMAIN. UPDATE NEW PANEL SCHEDULES ACCORDINGLY AND REPORT FINDING TO ENGINEER OF RECORD.
- PROVIDE NEW BRANCH CIRCUITS, PANEL FEEDERS AND DEVICES AS SHOWN ON THE PLANS OR AS REQUIRED FOR A COMPLETE OPERABLE SYSTEM, IN FULL ACCORDANCE AND COMPLIANCE WITH ALL APPLICABLE CODES.
- ALL EQUIPMENT WHICH IS DISCONNECTED AND REMOVED SHALL BE RETURNED TO THE OWNER OR THE OWNER SHALL BE PROVIDED SALVAGE VALUE OF SAID EQUIPMENT AT THE OWNER'S REQUEST. THE CONTRACTOR SHALL COORDINATE WITH THE OWNER FOR WHICH EQUIPMENT IS TO BE KEPT.
- FURNISH AND INSTALL ALL NECESSARY CONDUIT, WIRES, JUNCTION BOXES, BLANK COVER PLATES, ETCETERA, AT ALL LOCATIONS AFFECTED BY THE RELOCATION OF OUTLETS.
- WHERE INTERRUPTION OF A CIRCUIT FEEDING EXISTING EQUIPMENT OCCURS DUE TO NEW SCOPE OF WORK, THE CIRCUIT SHALL BE REHABILITATED AND MADE CONTINUOUS FROM PANEL TO LAST EXISTING OUTLET THAT REMAINS.
- THE CONTRACTOR SHALL REUSE EXISTING CONDUIT RUNS AND HOMERUNS WHERE POSSIBLE ACCORDING TO THE CODES THAT HAVE JURISDICTION. PULL NEW WIRES AS REQUIRED BY CODE AND THE AUTHORITY HAVING JURISDICTION.
- UPDATE ALL PANEL DIRECTORIES AT THE EXISTING PANELS TO REFLECT NEW WORK.
- THE CONTRACTOR SHALL FIELD VERIFY THE CONNECTED LOAD IN EXISTING FEEDERS AND BRANCH CIRCUITS THAT ARE AFFECTED BY THIS PROJECT'S SCOPE OF WORK PRIOR TO ADDING NEW LOAD TO EXISTING CONDUCTORS, CIRCUIT BREAKERS, PANELS, TRANSFORMERS AND SWITCHGEAR. NOTIFY THE ARCHITECT IMMEDIATELY IF ANY EXISTING EQUIPMENT IS FOUND TO BE OVERLOADED OR WILL BECOME SO IF NEW LOAD IS ADDED TO THE CIRCUIT OR FEEDER. REPORT ALL FINDINGS TO THE ENGINEER OF RECORD.
- THE DEMOLITION DRAWING, EXISTING PANEL SCHEDULE(S) AND EXISTING SINGLE LINE DIAGRAM(S) ARE BASED ON EXISTING DRAWINGS AND OWNER SUPPLIED INFORMATION. THERE HAS BEEN NO VERIFICATION OF PRECISE LOCATIONS, WIRING OR OPERATION OF EXISTING EQUIPMENT. THE CONTRACTORS SHALL VERIFY ALL JOB CONDITIONS PRIOR TO BID. THE CONTRACTORS SHALL THOROUGHLY EXAMINE AND VERIFY EXISTING CONDITIONS. ANY CONDITION FOUND UNACCEPTABLE OR IN VIOLATION OF CODES AND AUTHORITIES HAVING JURISDICTION SHALL BE CORRECTED.
- THE CONTRACTOR SHALL PERFORM ALL FIELD VERIFICATION, OBSERVATION, TESTING AND EXAMINATION WORK PRIOR TO ACTUAL CONSTRUCTION AND BREAKING NEW GROUND. A WRITTEN NOTICE SHALL BE ISSUED OF ALL FINDINGS TO THE ARCHITECT, LISTING MALFUNCTIONS, FAULTY EQUIPMENT AND DISCREPANCIES.
- THE CONTRACTOR SHALL PROVIDE ADDITIONAL LABOR AND MATERIALS REQUIRED TO ENSURE A COMPLETE AND OPERABLE SYSTEM IN ACCORDANCE WITH CODES AND ALL AUTHORITIES HAVING JURISDICTION. ALL NOTICE TO THE ARCHITECT SHALL BECOME PART OF THE CONTRACTOR'S WORK AS IF IT WERE INDICATED AND APPLIED ON THE CONSTRUCTION DOCUMENTS.
- THE CONTRACTOR SHALL INCLUDE IN THEIR BID ALL WORK AND COSTS ASSOCIATED WITH RELOCATING JUNCTION BOXES, PULL BOXES OR ANY OTHER DEVICE THAT IS RENDERED INACCESSIBLE AS A RESULT OF THE NEW WORK.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO STORE AND RE-USE ELECTRICAL SYSTEMS, INCLUDING LUMINAIRES, CONDUIT AND WIRING, WHERE POSSIBLE.
- REMOVE SURFACE MOUNTED OUTLETS, CONDUIT AND WIRING, ETCETERA, AND ABANDONED CONCEALED CONDUITS IN CONCRETE IN PLACE THAT ARE NO LONGER REQUIRED. ANY DEMOLITION OF WIRES TO BE PULLED OUT OF OVERHEAD AREA MUST BE COMPLETELY REMOVED AND NOT LEFT ABANDONED IN THE SPACES ABOVE DROP CEILINGS OR SIMILAR SPACES. ANY UNNEEDED EXISTING CONDUIT AND WIRING FOUND ABANDONED IN THE OVERHEAD CEILING SPACE SHALL BE COMPLETELY REMOVED.
- BRANCH CIRCUITRY WHICH IS NO LONGER IN USE SHALL BE REMOVED BACK TO THE SOURCE OR TO THE NEAREST DEVICE THAT WILL REMAIN IN SERVICE.
- PROVIDE NEW CIRCUIT IDENTIFICATION TO ALL EXISTING DEVICES THAT WILL REMAIN AFTER COMPLETION OF NEW SCOPE OF WORK.
- THE CONTRACTOR SHALL REPAIR AND/OR RE-PAINT ALL AREAS DAMAGED BY DEMOLITION OF CONSTRUCTION AND FINISH TO MATCH EXISTING ADJACENT SURFACES.
- THE CONTRACTOR SHALL PROTECT AND COVER ALL LUMINAIRES AND ELECTRICAL DEVICES IN AREAS AFFECTED BY NEW SCOPE OF WORK. UPON COMPLETION OF WORK, SHALL THOROUGHLY CLEAN ALL LUMINAIRES, EQUIPMENT, WALLS AND CEILING FROM DUST AND DEBRIS.
- THE CONTRACTOR SHALL INCLUDE ALL COSTS ASSOCIATED WITH CLEAN UP AND DISPOSAL OF EQUIPMENT NOT RETURNED TO THE OWNER. CONTRACTOR SHALL ALSO INCLUDE ALL COST ASSOCIATED WITH CLEAN UP AND DISPOSAL OF HAZARDOUS MATERIALS.



COORDINATE MEANS AND METHODS OF CONDUIT SYSTEM WITH ARCHITECT PRIOR TO ROUGH-IN

POWER & SIGNAL PLAN

SCALE: 1/4" = 1'-0"



POWER & SIGNAL PLAN REFERENCE NOTES:

- MAINTAIN MINIMUM CODE REQUIRED WORKING SPACE CLEARANCE OF 3'-0" ABOUT ELECTRICAL EQUIPMENT PER NEC ARTICLE 110.26.
- NO PIPING, DUCTS, LEAK PROTECTION APPARATUS, OR OTHER EQUIPMENT FOREIGN TO THE ELECTRICAL INSTALLATION SHALL BE ALLOWED IN THE DEDICATED SPACE ABOVE AND BELOW ELECTRICAL PANELS. THE SPACE EQUAL TO THE WIDTH AND DEPTH OF THE EQUIPMENT AND EXTENDING FROM THE FLOOR TO A HEIGHT OF 6 FEET ABOVE THE ELECTRICAL EQUIPMENT OR TO THE STRUCTURAL CEILING, WHICHEVER IS LOWER, SHALL BE DEDICATED TO THE ELECTRICAL INSTALLATION, PER NEC ARTICLE 110.26.
- EXISTING WALL OUTLETS INDICATED BY SCRIPT "(E)" ARE TO REMAIN. MAINTAIN EXISTING CIRCUIT CONTINUITY. FIELD VERIFY ALL LOCATIONS PRIOR TO BID. AS BUILD ELECTRICAL PLANS UPON COMPLETION OF CONSTRUCTION.
- CONTRACTOR TO COORDINATE RELOCATION OF EXISTING TELEPHONE SERVICE AND/OR NEW CABLE TV SERVICE TO THE PROPERTY WITH EXISTING UTILITY COMPANIES. PROVIDE AND INSTALL A CONDUIT RISER AND WEATHERHEAD PER RESPECTIVE UTILITY COMPANY REQUIREMENTS.
- CATV OUTLET. PROVIDE AND INSTALL A PLASTER RING OR JUNCTION BOX WITH 3/4" C.O. STUB UP TO ACCESSIBLE CEILING SPACE FOR DATA CABLEING BY OTHERS. CONFIRM FINAL LOCATION WITH ARCHITECT OR OWNER'S REP PRIOR TO ROUGH-IN.
- TELEPHONE/DATA OUTLET. PROVIDE AND INSTALL A PLASTER RING OR JUNCTION BOX WITH 3/4" C.O. STUB UP TO ACCESSIBLE CEILING SPACE OR LOW VOLTAGE RACEWAY SYSTEM FOR DATA CABLEING BY OTHERS. CONFIRM FINAL LOCATION WITH ARCHITECT OR OWNER'S REP PRIOR TO ROUGH-IN.
- KITCHEN EQUIPMENT. ELECTRICAL CONTRACTOR SHALL VERIFY LOCATION, CONNECTION SPECIFICATION AND MOUNTING HEIGHTS WITH VENDOR AND OWNER PRIOR TO ROUGH-IN.
- ALL 15 AND 20A 120V RECEPTACLES INSTALLED IN KITCHEN AND FOOD PREP AREAS SHALL BE GFCI PROTECTED AND "READILY ACCESSIBLE (NEC210.8)". ACCESSIBILITY TO RECEPTACLE SHALL NOT REQUIRE MOVEMENT OF EQUIPMENT AND/OR ANY ADDITIONAL TOOLS, LIKE A LADDER, IN ORDER TO GAIN ACCESS TO THE RECEPTACLE. IF RECEPTACLES ARE NOT ABLE TO BE LOCATED IN AN ACCESSIBLE SPACE, PROVIDE AND INSTALL A GFCI TYPE CIRCUIT BREAKER FOR THE CIRCUIT IN THIS SPACE.
- PROVIDE AND INSTALL NEW SURFACE MOUNTED RACEWAY BY WIREMOLD OR APPROVED EQUAL. TO BE STAINLESS STEEL AND LOCATED ABOUT COUNTERTOP. SEE ARCHITECTURAL ELEVATIONS FOR EXACT LOCATIONS AND LENGTH. RACEWAY TO BE SINGLE FOR POWER DEVICES ONLY.
- COUNTERTOP APPLIANCES, 120V-1ϕ. SEE ARCHITECTURAL ELEVATIONS FOR OUTLET HEIGHTS AND CONFIRM LOCATIONS WITH OWNER'S REP PRIOR TO ROUGH-IN.

E
ENGINEERS

CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709

BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED


SHEET SIZE: 24X36

DRAWING TITLE:

POWER AND SIGNAL PLAN

SHEET NO:

E400



BLDG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:



LIGHTING PLAN

SHEET NO:


E401

LIGHTING PLAN REFERENCE NOTES:

- 1 PROVIDE UNDERCABINET LIGHTS FOR COUNTER LIGHTING AND MINIMIZE GLARE BY PLACEMENT DIRECTED BY THE ARCHITECT. SEE ARCHITECTURAL DETAIL FOR MOUNTING METHOD AND LOCATION. PROVIDE SWITCH AS SHOWN ON ARCHITECTURAL DETAIL.
- 2 PROVIDE AND INSTALL A PDT WALL TYPE SWITCH OCCUPANCY SENSOR CONTROL DEVICE WITH ADEQUATE COVERAGE OF ROOM TO DIM LOAD. TO BE NLIGHT #NWSX-PDT-LV-DX-PDT-D SERIES WITH STAINLESS-STEEL COVER PLATE OR APPROVED EQUAL FOR 1 POLE (2-POLE VERSION NOT AVAILABLE). SEE FLOOR PLANS FOR REQUIRED POLES. CONTRACTOR TO CONFIRM DEVICE AND LUMINAIRE ARE COMPATIBLE PRIOR TO ORDER.
- 3 PROVIDE AND INSTALL A DUAL TECHNOLOGY CEILING TYPE OCCUPANCY SENSOR WITH LOW VOLTAGE WALL BOX DIMMER(S) WITH ADEQUATE COVERAGE OF ROOM. SENSOR TO BE NLIGHT #NCM-PDT-9-RJB SERIES WITH POWER PACK OR APPROVED EQUAL. DIMMER SWITCH TO BE NLIGHT #NPDM SERIES OR APPROVED EQUAL. CONTRACTOR TO CONFIRM DEVICE AND LUMINAIRE ARE COMPATIBLE PRIOR TO ORDER.
- 4 PROVIDE AND INSTALL DUAL TECHNOLOGY WIDE VIEW CEILING SENSORS FOR A HALLWAY APPLICATION. SENSOR TO BE NLIGHT #NCM-PDT-10-RJB SERIES OR APPROVED EQUAL. CONTRACTOR TO CONFIRM DEVICE AND LUMINAIRE ARE COMPATIBLE PRIOR TO ORDER.
- 5 ROOM IS EXEMPT FROM MULTI-LEVEL CONTROL REQUIREMENTS - ALL LIGHTS SHALL NOT BE DIMMED.
- 6 ROOM HAS A COMBINED TOTAL INSTALLED GENERAL LIGHTING POWER IN THE DAYLIT ZONES LESS THAN 120W. AUTOMATIC DAYLIGHTING CONTROL IS NOT REQUIRED.
- 7 BRANCH CIRCUIT TO BE ROUTED VIA THE EXISTING LIGHTING CONTROL PANEL FOR AUTOMATIC CONTROL OF LUMINAIRES. CONTRACTOR SHALL IDENTIFY CIRCUIT NUMBER IN THE FIELD AND CONFIRM CAPACITY IS AVAILABLE FOR THE NEW LED LIGHTING.
- 8 ALARM LIGHT. SEE SHEET E402 FOR BRANCH WIRE CIRCUITING. SEE DETAIL "A" ON SHEET E402 FOR SEQUENCE OF OPERATION AND TYPICAL WIRING DIAGRAM.
- 9 ELECTRICAL CONTRACTOR SHALL VERIFY ALL TYPES, QUANTITIES AND COMPATIBILITY OF SENSOR PLACEMENT AND SPECIFICATION WITH MANUFACTURER PRIOR TO ORDERING LIGHTING CONTROL SYSTEM.
- 10 LIGHTING CONTROL SYSTEM SHALL INCLUDE: 1) START-UP, 2) PROGRAMMING, 3) COMMISSIONING AND 4) END USER TRAINING.
- 11 PROVIDE A NON-SWITCHED HOT LEG OF DEDICATED FIRE ALARM BRANCH CIRCUIT TO ALL SINGLE STATION SMOKE ALARMS AND SMOKE DETECTORS AS THE PRIMARY SOURCE OF POWER. THE SECONDARY POWER SOURCE SHALL BE A LOCAL BATTERY.
- 12 LIGHT FIXTURES TO BE UNSWITCHED AND REMAIN "ON" FOR 24-HOUR OPERATION (NIGHT LIGHT). CONFIRM ALL FIXTURE LOCATIONS WITH OWNER'S REP PRIOR TO INSTALLING WIRING.
- 13 THE EXISTING FIRE ALARM CONTROL PANEL 120V-1 ϕ TO REMAIN. USE NEW BRANCH CIRCUIT AS INDICATED ON FLOOR PLANS AND MAKE ALL LINE VOLTAGE CONNECTIONS TO NEW SINGLE STATION SMOKE ALARMS. THE GENERAL CONTRACTOR TO PROVIDE A FIRE MARSHALL APPROVED FIRE ALARM SYSTEM. THE SYSTEM IS A DEFERRED SUBMITTAL. IF ALLOWED BY THE FIRE MARSHALL, SMOKE DETECTORS CAN BE WIRED TO THE LOCAL LIGHTING BRANCH CIRCUIT FOR PRIMARY POWER AND A LOCAL BATTERY FOR SECONDARY POWER. REPORT MEANS AND METHODS TO ENGINEER OF RECORD.
- 14 NEW SPEAKER LOCATIONS. EXTEND NEW LOW VOLTAGE WIRING TO THE EXISTING SPEAKER WIRING CONTROL PANEL AND FIELD VERIFY 120V-1 ϕ LINE VOLTAGE WIRING SOURCE. MAKE ALL LINE VOLTAGE CONNECTIONS TO CONTROL PANEL. SYSTEM TO BE "DESIGN BUILT" AND INCLUDE ALL FIRE STATION REQUIREMENTS.
- 15 CONTRACTOR TO FIELD VERIFY EXISTING CIRCUIT NUMBER USED FOR THE DEMOLISHED INTERIOR AND EXTERIOR LIGHTING FIXTURES. THIS CIRCUIT SHALL BE RE-USED FOR THE NEW LUMINAIRES. UPDATE PANEL SCHEDULES IN THE FIELD AND REPORT FINDING TO THE ENGINEER OF RECORD.



LIGHTING PLAN
SCALE: 1/4"=1'-0"





BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
△	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:

**ALARM LIGHTING & SMOKE
DETECTOR CIRCUITING PLAN**

SHEET NO:

E402

The schematic of the ring down system that turns the lights on in the dorm rooms when Fire receives a call.

SEQUENCE OF OPERATION:


1. When a call comes in from dispatch the momentary contacts to CR1 are closed energizing CR1.
2. CR1 contacts #43 & 44 will momentarily close energizing LC1 "latching on" the lights in the room.
3. CR1 contacts #13 & 14 will momentarily close energizing CR2.
4. CR2 contacts #13 & 14 will close to keep CR2 energized.
5. CR2 contacts #43 & 44 will close energizing TR.
6. Once 90 seconds have elapsed, TR contacts #9 & 6, NOTC, will close energizing LC1 "latching off" the lights in the room.
7. TR contacts #1 & 7, NCTO, will open de-energizing CR2.
8. CR2 contacts #43 & 44 open de-energizing TR.
9. System on stand by for next call.

Note: NOTC= Normally Open, Timed Closed
NCTO= Normally Closed, Timed Open

Prepared by:

Jim Fuentes
HVAC/Electrical Supervisor, General Services
City of Torrance | 20500 Madrona Avenue | Torrance, CA 90503 | 310.781.6951
Office | 310.625.7931 Cell | jfuentes@torranceca.gov | www.torranceca.gov

A SEQUENCE OF OPERATIONS





LEGEND


- ALARM LIGHT
- Ⓢ SPEAKER
- Ⓢ(D) SMOKE DETECTOR


SEE SHEET E401 FOR ALL

REFERENCE NOTES



**ALARM LIGHTING & SMOKE
DETECTOR CIRCUITING PLAN**
SCALE: 1/4"=1'-0"





CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW
2	09.08.21	ISSUED FOR PLAN CHECK

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:



ELECTRICAL ROOF PLAN

SHEET NO:


E403


ROOF PLAN REFERENCE NOTES:

- 1 OUTDOOR VARIABLE REFRIGERANT FLOW SPLIT SYSTEM HEAT PUMP 240V-1Ø 11MCA. PROVIDE AND INSTALL A LOCKABLE, WEATHERPROOF 30AS/15AF/2P HP RATED FUSED DISCONNECT SWITCH AND MAKE CONNECTION TO UNIT. CONFIRM FINAL UNIT LOCATION AND SPECIFICATION WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN. MAKE ALL LINE VOLTAGE CONNECTIONS TO INDOOR FAN COIL UNIT. OUTDOOR UNIT POWERS INDOOR FAN COIL.
- 2 ROUTE ALL CONDUITS TO ROOF-TOP MECHANICAL UNITS WITHIN ROOF TOP UNITS' FOOTPRINT AND HORIZONTALLY THROUGH ATTIC SPACE.
- 3 PROVIDE ALL LINE VOLTAGE BRANCH CIRCUIT WIRING AND ALL LOW VOLTAGE CONDUIT ONLY WITH PULL STRING FOR CONTROL OF MECHANICAL SYSTEMS AS DIRECTED BY MECHANICAL CONTRACTOR. USE WEATHERPROOF JUNCTION BOX(ES) IN OUTDOOR AREAS. SEE WIRING DIAGRAMS ON MECHANICAL DRAWINGS.
- 4 PROVIDE AND INSTALL A RECEPTACLE AND ENCLOSURE THAT IS WEATHERPROOF AND IS LISTED AS "EXTRA DUTY". THE RECEPTACLE SHALL BE LISTED AS WEATHER RESISTANT TYPE WITH INTEGRAL GFCI PROTECTION. LOCATION SHALL BE WITHIN 25' OF ALL MECHANICAL SYSTEMS ON THE ROOF OR GROUND FLOOR EXTERIOR AREAS.
- 5 MAINTAIN MINIMUM CODE REQUIRED WORKING SPACE CLEARANCE OF 3'-0" ABOUT ELECTRICAL EQUIPMENT, PER NEC ARTICLE 110.26. IN ADDITION, ALL DISCONNECT SWITCHES AND CIRCUIT BREAKER HANDLES SHALL BE INSTALLED SO THAT THE CENTER OF THE GRIP OF THE OPERATING HANDLE WHEN IN THE HIGHEST POSITION IS NOT MORE THAN 6'-7" A.F.F.




ELECTRICAL ROOF PLAN
SCALE: 1/4"=1'-0"





CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE: PANEL SCHEDULES

SHEET NO:

E500

PANEL A (NEW) TYPE RECESSED FULLY RATED: 22,000
VOLTAGE 120/240 VOLT 1-PH 3-W MAIN L.O. 200 AMPERE AIC AT 240V-1PH
LOCATION CAPTAINS HALLWAY BUS SIZE 200 AMPERE

DESCRIPTION	WATT (VA)		LTG	REC	MSC/ LCL	CKT	POLE	BKR	BKR	POLE	CKT	MSC/ REC	LTG	WATT (VA)		DESCRIPTION	
	A	B												A	B		
APPARATUS LTG 1	900		3			1	1	20				2				SPACE	
APPARATUS LTG 2	900		3			3	1	20				4				SPACE	
APPARATUS LTG 3	900		3			5	1	20	20	1	6	1	57	1075		LIVING AREA LTG	
APPARATUS LTG 4	1200		4			7	1	20	15	1	8	LOCK	9			ALARM LTG	
WAS TREE LTG	500		1			9	1	20	20	1	10		5	740		CPIN & HALL LTG	
HALL RESTROOM	900		5			11	1	20	20	1	12		2		360	DAY ROOM	
SPARE						13	1	20	15	1	14		1	2	640	KITCHEN HOOD	
HOSE TOWER LTG	800		5			15	1	15	20	1	16		1		1200	DISPOSER 1	
HOIST MOTOR	1120					17	2	30	15	1	18	J			240	HVAC CONTROLS	
LI SHIP	1120					19	/	/	/	15	1	20				816	HEATER FAN 1
CAPTAIN DORM	900		5			21	1	20	15	1	22					816	HEATER FAN 2
SPARE						23	1	20	20	1	24	LOCK	9	1		461	SMOKE DET/ FIRE
SPARE						25	1	15			26						SPACE
SPARE						27	1	15	20	1	28						SPACE
REFRIGERATOR 1	1440				GFCI	29	1	15	20	1	30		4		720		ADA RESTROOM
REFRIGERATOR 2	1440				GFCI	31	1	15	20	1	32		6		1080		DORM 1 AND 2
COFFEE POT	1200		2			33	1	20	20	1	34		6		1080		DORM 3 AND 4
DISHWASHER	1500				GFCI	35	1	20	20	1	36		3			540	DORM 5
KITCH GEN USE	540		3			37	1	20	20	1	38		1		1200		WASHER
MICROWAVE	1500		1			39	1	20	20	1	40		2			360	DYER GAS
SPARE						41	1	20	20	1	42		4		720		HALLWAY
SUB-TOTAL	7500	9360													7231	4920	SUB-TOTAL

LINE TOTALS:	14731	14280
LCL ADDER:	1399	1031
TOTAL VA:	16090	15311
TOTAL KVA LOAD:		31401
TOTAL AMP LOAD:		131 AMPERE

NOTES:
1) CONTRACTOR TO EXTEND AND RELOCATE ALL EXISTING BRANCH CIRCUITS IN PANEL TO NEW PANEL AND AT SAME LOCATION. FEEDER HAS BEEN UPGRADED.
2) PROVIDE 'GFCI' TYPE CIRCUIT BREAKERS WHERE NOTED IN THE COLUMN MARKED 'MISC' ABOVE.
3) OLD PANEL IS EQUIPPED WITH AN INTEGRAL LIGHT SWITCH CONTRACTOR TO PROVIDE NEW SWITCH IN ADJACENT JUNCTION BOX WITH RECESSED COVER PLATE.
4) CIRCUIT DESCRIPTION IN NON-BOLD FONT IMPLY EXISTING BRANCH CIRCUIT TO REMAIN.

PANEL DPA (NEW) TYPE INTEGRAL TO 'MSA' - NEMA '3R' FULLY RATED: 65K
VOLTAGE 120/240 VOLT 1-PH 3-W MAIN C/B 400 AMPERE AIC AT 240V-1PH
LOCATION EXTERIOR WALL - OLD GENSET RM BUS SIZE 400 AMPERE

DESCRIPTION	WATT (VA)		LTG	REC	MSC/ LCL	CKT	POLE	BKR	BKR	POLE	CKT	MSC/ REC	LTG	WATT (VA)		DESCRIPTION
	A	B												A	B	
(N) PANEL 'C' VIA TRANSFER SW.	12933					1	2	150			2					UNUSABLE SPACE
(EX.) PANEL 'NP' VIA TRANSFER SW.	24840	12753				3	/	/			4					UNUSABLE SPACE
SPACE		23186				5	2	225			6					UNUSABLE SPACE
SPACE						7	/	/			8					UNUSABLE SPACE
SPACE						9					10					SPACE
SPACE						11					12					SPACE
SPACE						13					14					SPACE
SPACE						15					16					SPACE
SPACE						17					18					SPACE
SPACE						19					20					SPACE
SPACE						21					22					SPACE
SPACE						23					24					SPACE
SUB-TOTAL	37773	35939												0	0	SUB-TOTAL

LINE TOTALS:	37773	35939
LCL ADDER:		
TOTAL VA:	37773	35939
TOTAL KVA LOAD:		73712
TOTAL AMP LOAD:		307 AMPERE

NOTES:
1) CONTRACTOR CAN PROVIDE A MAIN BREAKER RATED FOR 80% OF CONNECTED LOAD AS A COST SAVINGS.

PANEL C (NEW) TYPE SURFACE FULLY RATED: 65K
VOLTAGE 120/240 VOLT 1-PH 3-W MAIN L.O. 200 AMPERE AIC AT 240V-1PH
LOCATION MAIN ELECTRICAL ROOM BUS SIZE 200 AMPERE

DESCRIPTION	WATT (VA)		LTG	REC	MSC/ LCL	CKT	POLE	BKR	BKR	POLE	CKT	MSC/ REC	LTG	WATT (VA)		DESCRIPTION
	A	B												A	B	
(RED TAPED) SPARE (F.V.)	1800	1800				1	2	20	20	2	2				1200	EXIST. FIRE TRUCK
EXIST. OFFICE	1800				HACR	5	2	30	30	2	6				1800	EXIST. AIR
HVAC	1800					7	/	/	/	/	8				1800	COMPRESSOR
EXIST. BUNK	2400				HACR	9	2	50	30	2	10	HACR			1800	EXIST. KITCHEN
HVAC	2400					11	/	/	/	/	12				1800	HVAC
NEW BUNK AC	1353				HACR	13	2	15	15	1	14		1		180	NEW SERVICE 1
(VFR-1) SPARE	1353					15	/	/	/	/	16					SPACE
SPARE						17	2	15			18					SPACE
SPARE						19	/	/	/	/	20					SPACE
SPARE						21					22					SPACE
SPARE						23					24					SPACE
SPARE						25					26					SPACE
SPARE						27					28					SPACE
SPARE						29					30					SPACE
SUB-TOTAL	7353	7353												4980	4800	SUB-TOTAL

LINE TOTALS:	12333	12153
LCL ADDER:	600	600
TOTAL VA:	12933	12753
TOTAL KVA LOAD:		25686
TOTAL AMP LOAD:		107 AMPERE

NOTES:
1) CONTRACTOR TO EXTEND AND RELOCATE ALL EXISTING BRANCH CIRCUITS IN PANEL TO NEW PANEL AND AT NEW LOCATION.
2) PROVIDE 'HACR' RATED CIRCUIT BREAKERS WHERE NOTED IN THE COLUMN MARKED 'MISC' ABOVE.

PANEL NP (EXISTING) TYPE SURFACE - NEMA '3R' FULLY RATED: 65K
VOLTAGE 120/240 VOLT 1-PH 3-W MAIN L.O. 225 AMPERE AIC AT 240V-1PH
LOCATION EXTERIOR WALL - OLD GENSET RM BUS SIZE 225 AMPERE

DESCRIPTION	WATT (VA)		LTG	REC	MSC/ LCL	CKT	POLE	BKR	BKR	POLE	CKT	MSC/ REC	LTG	WATT (VA)		DESCRIPTION
	A	B												A	B	
PANEL 'B'	5000					1	2	100	20	1	2			1500		BATT CHRGR & PMP
SPARE		5000				3	/	/	20	1	4				1000	ALERT US
SPARE						5	2	50	20	2	6			1500		GENSET BLOCK
SPARE						7	/	/	/	/	8				1500	HEATER
SPACE						9					10					SPACE
SPACE						11					12					SPACE
SPACE						13					14					SPACE
SPACE						15					16					SPACE
SPACE						17					18					SPACE
SPACE						19					20					SPACE
SPACE						21					22					SPACE
SPACE						23					24					SPACE
SPACE						25					26					SPACE
SPACE						27					28					SPACE
SPACE						29					30					SPACE
SPACE						31					32					SPACE
SPACE						33					34					SPACE
SPACE						35					36					SPACE
SPACE						37					38					SPACE
SPACE						39					40					SPACE
SPACE						41					42					SPACE
UNUSABLE SPACE						X	X	X	X	X	X					UNUSABLE SPACE
BOTTOM FEEDER BRAKER						175	Z(N)	44			44			16090		NEW PANEL 'A'
SUB-TOTAL	5000	5000												16090	17811	SUB-TOTAL


LINE TOTALS:	16090	17811
LCL ADDER:	750	375
TOTAL VA:	24840	23186
TOTAL KVA LOAD:		48026
TOTAL AMP LOAD:		200 AMPERE

NOTES:
1) CUTLER HAMMER TYPE PRL2a PANELBOARD AND DATED 08-03-2001.
2) PANEL 'B' CONNECTED LOAD IS AN ESTIMATE AND FOR DESIGN DEVELOPMENT PURPOSES ONLY. SEE SHEET E304 FOR WORST-CASE ANALYSIS.

GENERAL NOTES FOR BRANCH CIRCUIT WIRING:

- CONDUCTORS OF A MULTI-WIRE BRANCH CIRCUIT SHALL ORIGINATE FROM THE SAME PANELBOARD. THE BRANCH CIRCUIT SHALL BE PROVIDED WITH A MEANS THAT WILL SIMULTANEOUSLY DISCONNECT ALL UNGROUNDED CONDUCTORS AT THE POINT WHERE THE BRANCH CIRCUIT ORIGINATES.
- ALL 2-POLE CIRCUIT BREAKERS AND ALL 3-POLE CIRCUIT BREAKERS IN PANELBOARDS SHALL BE RATED FOR DUAL VOLTAGE 120/208V [NEC 240.86]. SEE POLE COLUMN OF PANEL SCHEDULE FOR NOTATION '2' AND '3'.
- RECEPTACLES INSTALLED IN KITCHEN, FOOD PREP AREAS AND LOCKER ROOMS SHALL BE GFCI PROTECTED AND "READILY ACCESSIBLE" [NEC 210.8(B)]. ACCESSIBILITY TO RECEPTACLE SHALL NOT REQUIRE MOVEMENT OF EQUIPMENT AND/OR ANY ADDITIONAL TOOLS, LIKE A LADDER, IN ORDER TO GAIN ACCESS TO THE RECEPTACLE. IF RECEPTACLE ARE NOT ABLE TO BE LOCATED IN AN ACCESSIBLE SPACE, PROVIDE AND INSTALL A GFCI TYPE CIRCUIT BREAKER FOR THE CIRCUIT IN THIS AREA.
- APPLIANCE CIRCUITS GREATER THAN 300VA OR 1/8 HP SHALL HAVE A DISCONNECTING MEANS WITHIN SIGHT OF THE APPLIANCE [NEC 422.31 (B) (C)]. IF NOT WITHIN SIGHT, PROVIDE AND INSTALL A CIRCUIT BREAKER IN THE PANEL SCHEDULE THAT IS CAPABLE OF BEING LOCKED IN THE OPEN POSITION. THE PROVISIONS FOR LOCKING SHALL REMAIN IN PLACE WITH OR WITHOUT THE LOCK INSTALLED [NEC 110.25]. SEE 'MISC' COLUMN OF PANEL SCHEDULE FOR NOTATION 'LOCK'.
- PROVIDE A LOCK ON DEVICE AT CIRCUIT BREAKER HANDLE FOR FIRE ALARM SIGNAL SYSTEMS. SEE MISC COLUMN OF PANEL SCHEDULE FOR NOTATION 'LOCK' [NFPA 72].
- SIZE NO. 1 AWG CONDUCTORS AND SMALLER ARE TO USE THE 60-DEGREE COLUMN OF TABLE 310.15(B)(16) TO DETERMINE AMPACITY. CONDUCTORS #1/0 AWG AND LARGER ARE TO USE THE 75-DEGREE COLUMN OF THE TABLE TO DETERMINE AMPACITY OF THE CONDUCTOR. SEE UL ELECTRICAL CONSTRUCTION MATERIALS DIRECTORY AND NEC ARTICLE 110.14(C).
- ALL CONDUCTORS SHALL BE COPPER AND RATED FOR 90 DEGREE CELSIUS AND 600V. SIZES NO. 8 AWG AND LARGER SHALL BE STRANDED AND NO. 10 AWG AND SMALLER SHALL BE SOLID. USE TYPE THHN/THWN-2/XHHW/XHHW-2.
- ALL CIRCUIT BREAKERS SHALL BE BOLT ON TYPE.

**PROTECTIVE BARRIERS
FOR UNDERGROUND DISTRIBUTION STRUCTURES
SEE UCS MS 830**



- BARRIER:**
TO BE ONE OF THE FOLLOWING:
- 1" GALV STEEL PIPE (1/4" MIN WALL) FILLED WITH CONCRETE
 - RAILROAD RAIL (50 LB MIN) OR 3 1/2" PER FOOT AMERICAN STD BEAM (2" x 3" x 1/2")
 - 8" x 8" REINFC CONCRETE
 - SPECIAL BARRIERS BY PRIOR SEE CO. APPROVAL

- NOTES:**
1. STRUCTURES WILL NORMALLY BE INSTALLED ONLY IN NON-TRAFFIC AREAS. BARRIERS TO BE USED WHERE CONSTRUCTION HAS EXPOSED EQUIPMENT TO TRAFFIC.
 2. TOP OF BARRIERS TO BE SMOOTH CUT AND TOP EDGES TO BE ROUNDED.
 3. ONE BARRIER TO BE REMOVABLE WHEN OBSTACLES PREVENT EQUIPMENT REMOVAL BY CRANE.
 4. ADEQUATE CLEARANCE MUST BE PROVIDED FOR DOORS, COOLING RADIATORS, ETC.
 5. BARRICADES, AS SHOWN, INDICATE TYPICAL REQUIREMENTS. FIELD CONDITIONS WILL NECESSITATE CHANGES FOR ADEQUATE EQUIPMENT PROTECTION. APPROVAL IN THE FIELD FROM THE UNDERGROUND INSPECTOR IS REQUIRED FOR ALL BARRICADE INSTALLATIONS.
 6. WHEN SPECIFIED ON WORKING DRAWING, A 6" (MINIMUM HEIGHT) CURB MAY BE INSTALLED IN PLACE OF BARRIERS. THIS CURB MUST BE AT LEAST 6" THICK AND ITS FRONT FACE LOCATED 60" MINIMUM (OR AS SPECIFIED ON DRAWING) FROM THE EQUIPMENT FOUNDATION.
 7. INCREASE TO 4" MINIMUM AT FRONT OF FRAGMENT OF TRANSFORMERS AND CAPACITORS; AND 38" MINIMUM AT BACK OF CAPACITORS (DOOR SIDE ONLY), WHEN A 72" x 94" PAD IS BEING INSTALLED.

D911 Rev. 01/21/09



Response to Letter of Request for Short Circuit Current Values

To: 5205 CALLE MAYOR
TORRANCE CA 90505

From: Southern California Edison
505 Maple Ave
Torrance CA 90503


Subject: Southern California Edison's Contribution to Short Circuit Current at the Point of Connection of the Company's Service Conductors to the Customer's Service Entrance Facilities.

Project Name: TORRANCE FIRE STATION NO. 4
Address: 5205 CALLE MAYOR TORRANCE CA 90505

- (1) The voltage to be utilized for this project will be 120/240V, to serve your 400A main switch/switches.
- (2) Southern California Edison's Contribution to Short Circuit Current at the point of calculation, based on Southern California Edison's demand factors for transformer sizing, will be approximately 42,000A (symmetrical).

Service Cables: 350
Distance from Transformer: 121'
Transformer: 50 kva

Jesus Fernandez
Jesus Fernandez - Service Planner Date



- Notes(s):**
1. A minimum of 3 feet of clear, level concrete workspace is required in front of all termination, metering, and service equipment.
 2. See ESR-5 for Meter-Mounting Height Requirements. Meter-mounting height will be measured from the standing and working space to the centerline of the meter(s).
 3. When service equipment is installed on an elevated portion of the floor/ground, or housekeeping pad, the pad shall be flush with the bottom of the service equipment and extend a minimum of three feet. This is measured from the front of the service equipment or the outer door(s) of the switchboard NEMA 3R enclosure when installed. In no case shall the maximum meter height of 6'-3" be exceeded.
 4. To maintain a safe, clear, and level concrete working area in front of new or existing meter and service equipment, a concrete slab, acceptable to the Company, must be used.
 5. For switchboards above 600 V, five-foot minimum of clear and level concrete standing and working space is required in the front, rear, and side of any section where such part supports or provides access to metering, testing equipment, or service cable termination sections.

16.12 Protective Barriers for Service Equipment


Barrier posts are used to protect the meter and service equipment, as well as personnel, from vehicular contact, and to prohibit encroachment into the working space (for example, loading zones, driveways, congested areas, off street parking, and so on).

The customer shall provide and install "non-removable" barriers to provide the proper safe working clearances where the workspace is exposed to vehicular or other hazardous conditions. Meters will not be set until the barriers have been installed.

EFFECTIVE DATE	4-27-2018	Underground Service Connections 0-600 V	ESR-3
APPROVED	<i>a/f</i>	Electrical Service Requirements ► SCE Public ◀	PAGE 3-20



Figure 3-3: Protective Barrier for Service Equipment Installation Requirements




- Notes(s):**
1. Meters located on a wall adjacent to any parking area, or area accessible to vehicular traffic, shall be protected by non-removable barriers. Wheel stops and removable barriers are not acceptable substitutes. Maintain a minimum of three feet of clear and level working space in front of all the service equipment enclosures. Barriers must be so positioned as to allow all service equipment doors/panels to be opened 90 degrees.
 2. Use four-inch galvanized steel pipe (1/4-inch minimum wall) filled with concrete.
 3. The concrete encasement shall be a minimum of six inches thick in stable soil and 12 inches thick in sandy or unstable soil.
 4. Barriers must be installed in line with each end of the service equipment to prevent vehicle contact. The distance between barriers shall not exceed 4'-6\".
 5. Before excavating for the barriers, call DIG ALERT at 1-811-227-2600 for mark-out service. Call at least 48 hours prior to excavating.
 6. See Figure 3-2.

EFFECTIVE DATE	4-27-2018	Underground Service Connections 0-600 V	ESR-3
APPROVED	<i>a/f</i>	Electrical Service Requirements ► SCE Public ◀	PAGE 3-21




Figure 5-4: Separation of Meter Assemblies for Electric and Gas Services



- Notes(s):**
1. Size and dimensions of panels will vary. Drawings are not to scale.
 2. This drawing pertains to both overhead and underground electric service applications.
 3. Maintain a 3-foot clear, level, and unobstructed workspace in front of electric service equipment.
 4. Plumbing fixtures that extend more than 6 inches out from wall surface must be located 18 inches minimum from the outside edge of the meter panel.
 5. For new construction only, does not apply for upgrades.
 6. Upgrades and replacements — Line Side Panels that are currently installed 24 inches or greater from the line side of the gas meter, clearance may not be reduced. Panels that are currently installed less than 24 inches from the gas meter, may remain (or be re-installed) in existing location.
 7. Upgrades and replacements — Load Side Panels that are currently installed 18 inches or greater from the load side of the gas meter, clearance may not be reduced. Panels that are currently installed less than 18 inches from the gas meter, may remain (or be re-installed) in existing location.

EFFECTIVE DATE	10-27-2017	Meters — EXO Installations	ESR-5
APPROVED	<i>A. E.</i>	Electrical Service Requirements ► SCE Public ◀	PAGE 5-19



CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
△	06.xx.21	ISSUED FOR PLAN CHECK
	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented thereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions. Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to this office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP


DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:
SCE SHORT CIRCUIT
DUTY LETTER AND DETAILS

SHEET NO:

E600



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
06.x.x.21		ISSUED FOR PLAN CHECK
06.02.21		ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disseminated to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Virtual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24X36

DRAWING TITLE:

SCS MAP AND DETAILS

SHEET NO:

E601

CREW & CUSTOMER MAP - TD# 1856232

CONTACTS:
CALL LOUIS ORTEGA FOR ACCESS THRU GATE
LOUIS ORTEGA 310-953-1355
ERIC PERCIC 424-272-6709

CONSTRUCTION NOTES:

Unless otherwise specified on the working drawing which forms a part of the specifications, the Contractor/Developer shall furnish the following items at no cost to the Edison Company:

1. GENERAL SPECIFICATIONS SEE USCS 0100.
2. CONDUIT:
 - a. Minimum cover in street or alleyway is 36" below gutter grade, unless noted otherwise.
 - b. Minimum cover on surface proximate to 30" below ground grade, unless noted otherwise.
 - c. Construction materials and installation methods shall conform to the specifications per USCS 100.1, 110 AND 120.
 - d. For the type of conduit for this job, See USCS 0101.1.
 - e. Install all runs per USCS 0102.
 - f. Install all runs per USCS 0103.
 - g. Cap all non-metallic conduits per USCS 0104 and service conduits per USCS 0105.
 - h. Install flexible conduit in all conduits terminating into vaults, manholes, pits, etc. at all cop locations, per USCS 0106.1 & USCS 0105.2.
 - i. Install full wrap to be at least 3/8" polypropylene rope, braided or twisted.
 - j. For specifications, approved makes, and suppliers, see USCS 0107.
3. ALL conduit must be installed with the approved material USCS 0101.

CONDUIT RADIUS REQUIREMENTS:

- a. The minimum radius for bends are:
 - 36" for conduits 4" and smaller
 - 48" for conduits 4" and 2" in diameter
 - 60" for 4" diameter conduit
 - 72" for 6" diameter conduit
- b. The minimum radius for all sweeps of all metallic conduits is 12'-6" (unless noted otherwise).

EXCAVATION AND BACKFILL:

1. Back area shall be cleared and rough graded to within four inches of final grade prior to installation of Edison conduit or structures.
2. All excavations shall be in accordance with the California State Construction Safety Orders (when applicable), Edison specifications, and all opening local ordinances.
3. Each trench to be a uniform depth below final grade prior to installation of Edison conduit or structures. Backfill shall be provided by the Contractor for all excavations and shall include crushed rock, concrete, and/or rip-rap backfill as required.
4. Backfill with a minimum of one sack per yard sand cement slurry around and over vaults and manholes per USCS 0109, unless otherwise noted.
5. A level working and standing surface, clear and unobstructed, entirely on the property of the customer, shall be provided. THE MINIMUM WIDTH OF THE WORKSPACE SHALL BE 36" INCHES OVERALL; BUT NEED NOT BE COVERED BENEATH THE METER. THE MINIMUM DEPTH OF THE WORKSPACE SHALL BE 36" INCHES. WHERE METERS ARE ENCLOSED IN A CLOSET OR RECESS IN AN ENCLOSURE, THE DEPTH OF THE WORKSPACE IS MEASURED FROM THE OUTER FACE OF THE CLOSET OR RECESS. THE MINIMUM HEIGHT OF THE WORKSPACE SHALL BE 78" INCHES.
6. Backfill with a minimum of one sack per yard sand cement slurry around and over vaults and manholes per USCS 0109, unless otherwise noted.
7. A level working and standing surface, clear and unobstructed, entirely on the property of the customer, shall be provided. THE MINIMUM WIDTH OF THE WORKSPACE SHALL BE 36" INCHES OVERALL; BUT NEED NOT BE COVERED BENEATH THE METER. THE MINIMUM DEPTH OF THE WORKSPACE SHALL BE 36" INCHES. WHERE METERS ARE ENCLOSED IN A CLOSET OR RECESS IN AN ENCLOSURE, THE DEPTH OF THE WORKSPACE IS MEASURED FROM THE OUTER FACE OF THE CLOSET OR RECESS. THE MINIMUM HEIGHT OF THE WORKSPACE SHALL BE 78" INCHES.
8. Backfill with a minimum of one sack per yard sand cement slurry around and over vaults and manholes per USCS 0109, unless otherwise noted.
9. A level working and standing surface, clear and unobstructed, entirely on the property of the customer, shall be provided. THE MINIMUM WIDTH OF THE WORKSPACE SHALL BE 36" INCHES OVERALL; BUT NEED NOT BE COVERED BENEATH THE METER. THE MINIMUM DEPTH OF THE WORKSPACE SHALL BE 36" INCHES. WHERE METERS ARE ENCLOSED IN A CLOSET OR RECESS IN AN ENCLOSURE, THE DEPTH OF THE WORKSPACE IS MEASURED FROM THE OUTER FACE OF THE CLOSET OR RECESS. THE MINIMUM HEIGHT OF THE WORKSPACE SHALL BE 78" INCHES.
10. Backfill with a minimum of one sack per yard sand cement slurry around and over vaults and manholes per USCS 0109, unless otherwise noted.
11. A level working and standing surface, clear and unobstructed, entirely on the property of the customer, shall be provided. THE MINIMUM WIDTH OF THE WORKSPACE SHALL BE 36" INCHES OVERALL; BUT NEED NOT BE COVERED BENEATH THE METER. THE MINIMUM DEPTH OF THE WORKSPACE SHALL BE 36" INCHES. WHERE METERS ARE ENCLOSED IN A CLOSET OR RECESS IN AN ENCLOSURE, THE DEPTH OF THE WORKSPACE IS MEASURED FROM THE OUTER FACE OF THE CLOSET OR RECESS. THE MINIMUM HEIGHT OF THE WORKSPACE SHALL BE 78" INCHES.
12. Backfill with a minimum of one sack per yard sand cement slurry around and over vaults and manholes per USCS 0109, unless otherwise noted.
13. A level working and standing surface, clear and unobstructed, entirely on the property of the customer, shall be provided. THE MINIMUM WIDTH OF THE WORKSPACE SHALL BE 36" INCHES OVERALL; BUT NEED NOT BE COVERED BENEATH THE METER. THE MINIMUM DEPTH OF THE WORKSPACE SHALL BE 36" INCHES. WHERE METERS ARE ENCLOSED IN A CLOSET OR RECESS IN AN ENCLOSURE, THE DEPTH OF THE WORKSPACE IS MEASURED FROM THE OUTER FACE OF THE CLOSET OR RECESS. THE MINIMUM HEIGHT OF THE WORKSPACE SHALL BE 78" INCHES.

PAVING:

1. Paving, where required, shall be placed in such a manner that interference with traffic, including pedestrian traffic, will be kept to a minimum. The Contractor shall establish a program of paving acceptable to the Municipality, County, or other authority having jurisdiction and which is acceptable to Edison.

STRUCTURES:

- a. All structures shall be constructed or installed to Edison specifications.
- b. Inside protection barriers per USCS 830 shall be installed in areas exposed to traffic, per Edison Inspector.
- c. All conduits lines and concrete floor structures shall be water tight.
- d. All grouting materials shall be furnished and installed by the Contractor.

RETAINING WALLS:

1. When required, retaining walls shall be provided by the Developer. Retaining walls are required wherever grade rises more than 18 inches above the structure or 12 inches above the top surface of a driveway of 5 feet from the same, or to retain adjacent driveways. Design and installation must comply with local building ordinances.
2. Retain walls shall be constructed in accordance with the California State Construction Safety Orders (when applicable), Edison specifications, and all opening local ordinances.

PERMITS:

1. All permits necessary for excavation shall be provided by the Contractor/Developer.

ACCESS:

1. Heavy truck access shall be maintained to equipment locations. Structures must be clear of all appurtenances that would obstruct the loading or unloading of equipment.

SERVICES:

1. Meters and services shall comply with Edison Electrical Services Requirements.
2. Meters must be in accordance with applicable local ordinances and approved by local inspection authorities.

LOCATION:

1. The location of excavations and structures for Edison shall be as shown on the working drawing. No deviation from the planned location will be permitted unless approved by the Edison Inspector. See USCS 0101, section 2.2.
2. Actual location of obstructions, storm drains, and/or other foreign utilities to be the responsibility of the Contractor. See USCS 0102, section 2.3.


CONTRACTOR:

1. Contractor is to verify location and width of all sidewalks and alleyways prior to street light installation. See USCS 0101, USCS 0102, USCS 0103, USCS 0104, USCS 0105, USCS 0106, USCS 0107, USCS 0108, USCS 0109, USCS 0110, USCS 0111, USCS 0112, USCS 0113, USCS 0114, USCS 0115, USCS 0116, USCS 0117, USCS 0118, USCS 0119, USCS 0120, USCS 0121, USCS 0122, USCS 0123, USCS 0124, USCS 0125, USCS 0126, USCS 0127, USCS 0128, USCS 0129, USCS 0130, USCS 0131, USCS 0132, USCS 0133, USCS 0134, USCS 0135, USCS 0136, USCS 0137, USCS 0138, USCS 0139, USCS 0140, USCS 0141, USCS 0142, USCS 0143, USCS 0144, USCS 0145, USCS 0146, USCS 0147, USCS 0148, USCS 0149, USCS 0150, USCS 0151, USCS 0152, USCS 0153, USCS 0154, USCS 0155, USCS 0156, USCS 0157, USCS 0158, USCS 0159, USCS 0160, USCS 0161, USCS 0162, USCS 0163, USCS 0164, USCS 0165, USCS 0166, USCS 0167, USCS 0168, USCS 0169, USCS 0170, USCS 0171, USCS 0172, USCS 0173, USCS 0174, USCS 0175, USCS 0176, USCS 0177, USCS 0178, USCS 0179, USCS 0180, USCS 0181, USCS 0182, USCS 0183, USCS 0184, USCS 0185, USCS 0186, USCS 0187, USCS 0188, USCS 0189, USCS 0190, USCS 0191, USCS 0192, USCS 0193, USCS 0194, USCS 0195, USCS 0196, USCS 0197, USCS 0198, USCS 0199, USCS 0200, USCS 0201, USCS 0202, USCS 0203, USCS 0204, USCS 0205, USCS 0206, USCS 0207, USCS 0208, USCS 0209, USCS 0210, USCS 0211, USCS 0212, USCS 0213, USCS 0214, USCS 0215, USCS 0216, USCS 0217, USCS 0218, USCS 0219, USCS 0220, USCS 0221, USCS 0222, USCS 0223, USCS 0224, USCS 0225, USCS 0226, USCS 0227, USCS 0228, USCS 0229, USCS 0230, USCS 0231, USCS 0232, USCS 0233, USCS 0234, USCS 0235, USCS 0236, USCS 0237, USCS 0238, USCS 0239, USCS 0240, USCS 0241, USCS 0242, USCS 0243, USCS 0244, USCS 0245, USCS 0246, USCS 0247, USCS 0248, USCS 0249, USCS 0250, USCS 0251, USCS 0252, USCS 0253, USCS 0254, USCS 0255, USCS 0256, USCS 0257, USCS 0258, USCS 0259, USCS 0260, USCS 0261, USCS 0262, USCS 0263, USCS 0264, USCS 0265, USCS 0266, USCS 0267, USCS 0268, USCS 0269, USCS 0270, USCS 0271, USCS 0272, USCS 0273, USCS 0274, USCS 0275, USCS 0276, USCS 0277, USCS 0278, USCS 0279, USCS 0280, USCS 0281, USCS 0282, USCS 0283, USCS 0284, USCS 0285, USCS 0286, USCS 0287, USCS 0288, USCS 0289, USCS 0290, USCS 0291, USCS 0292, USCS 0293, USCS 0294, USCS 0295, USCS 0296, USCS 0297, USCS 0298, USCS 0299, USCS 0300, USCS 0301, USCS 0302, USCS 0303, USCS 0304, USCS 0305, USCS 0306, USCS 0307, USCS 0308, USCS 0309, USCS 0310, USCS 0311, USCS 0312, USCS 0313, USCS 0314, USCS 0315, USCS 0316, USCS 0317, USCS 0318, USCS 0319, USCS 0320, USCS 0321, USCS 0322, USCS 0323, USCS 0324, USCS 0325, USCS 0326, USCS 0327, USCS 0328, USCS 0329, USCS 0330, USCS 0331, USCS 0332, USCS 0333, USCS 0334, USCS 0335, USCS 0336, USCS 0337, USCS 0338, USCS 0339, USCS 0340, USCS 0341, USCS 0342, USCS 0343, USCS 0344, USCS 0345, USCS 0346, USCS 0347, USCS 0348, USCS 0349, USCS 0350, USCS 0351, USCS 0352, USCS 0353, USCS 0354, USCS 0355, USCS 0356, USCS 0357, USCS 0358, USCS 0359, USCS 0360, USCS 0361, USCS 0362, USCS 0363, USCS 0364, USCS 0365, USCS 0366, USCS 0367, USCS 0368, USCS 0369, USCS 0370, USCS 0371, USCS 0372, USCS 0373, USCS 0374, USCS 0375, USCS 0376, USCS 0377, USCS 0378, USCS 0379, USCS 0380, USCS 0381, USCS 0382, USCS 0383, USCS 0384, USCS 0385, USCS 0386, USCS 0387, USCS 0388, USCS 0389, USCS 0390, USCS 0391, USCS 0392, USCS 0393, USCS 0394, USCS 0395, USCS 0396, USCS 0397, USCS 0398, USCS 0399, USCS 0400, USCS 0401, USCS 0402, USCS 0403, USCS 0404, USCS 0405, USCS 0406, USCS 0407, USCS 0408, USCS 0409, USCS 0410, USCS 0411, USCS 0412, USCS 0413, USCS 0414, USCS 0415, USCS 0416, USCS 0417, USCS 0418, USCS 0419, USCS 0420, USCS 0421, USCS 0422, USCS 0423, USCS 0424, USCS 0425, USCS 0426, USCS 0427, USCS 0428, USCS 0429, USCS 0430, USCS 0431, USCS 0432, USCS 0433, USCS 0434, USCS 0435, USCS 0436, USCS 0437, USCS 0438, USCS 0439, USCS 0440, USCS 0441, USCS 0442, USCS 0443, USCS 0444, USCS 0445, USCS 0446, USCS 0447, USCS 0448, USCS 0449, USCS 0450, USCS 0451, USCS 0452, USCS 0453, USCS 0454, USCS 0455, USCS 0456, USCS 0457, USCS 0458, USCS 0459, USCS 0460, USCS 0461, USCS 0462, USCS 0463, USCS 0464, USCS 0465, USCS 0466, USCS 0467, USCS 0468, USCS 0469, USCS 0470, USCS 0471, USCS 0472, USCS 0473, USCS 0474, USCS 0475, USCS 0476, USCS 0477, USCS 0478, USCS 0479, USCS 0480, USCS 0481, USCS 0482, USCS 0483, USCS 0484, USCS 0485, USCS 0486, USCS 0487, USCS 0488, USCS 0489, USCS 0490, USCS 0491, USCS 0492, USCS 0493, USCS 0494, USCS 0495, USCS 0496, USCS 0497, USCS 0498, USCS 0499, USCS 0500, USCS 0501, USCS 0502, USCS 0503, USCS 0504, USCS 0505, USCS 0506, USCS 0507, USCS 0508, USCS 0509, USCS 0510, USCS 0511, USCS 0512, USCS 0513, USCS 0514, USCS 0515, USCS 0516, USCS 0517, USCS 0518, USCS 0519, USCS 0520, USCS 0521, USCS 0522, USCS 0523, USCS 0524, USCS 0525, USCS 0526, USCS 0527, USCS 0528, USCS 0529, USCS 0530, USCS 0531, USCS 0532, USCS 0533, USCS 0534, USCS 0535, USCS 0536, USCS 0537, USCS 0538, USCS 0539, USCS 0540, USCS 0541, USCS 0542, USCS 0543, USCS 0544, USCS 0545, USCS 0546, USCS 0547, USCS 0548, USCS 0549, USCS 0550, USCS 0551, USCS 0552, USCS 0553, USCS 0554, USCS 0555, USCS 0556, USCS 0557, USCS 0558, USCS 0559, USCS 0560, USCS 0561, USCS 0562, USCS 0563, USCS 0564, USCS 0565, USCS 0566, USCS 0567, USCS 0568, USCS 0569, USCS 0570, USCS 0571, USCS 0572, USCS 0573, USCS 0574, USCS 0575, USCS 0576, USCS 0577, USCS 0578, USCS 0579, USCS 0580, USCS 0581, USCS 0582, USCS 0583, USCS 0584, USCS 0585, USCS 0586, USCS 0587, USCS 0588, USCS 0589, USCS 0590, USCS 0591, USCS 0592, USCS 0593, USCS 0594, USCS 0595, USCS 0596, USCS 0597, USCS 0598, USCS 0599, USCS 0600, USCS 0601, USCS 0602, USCS 0603, USCS 0604, USCS 0605, USCS 0606, USCS 0607, USCS 0608, USCS 0609, USCS 0610, USCS 0611, USCS 0612, USCS 0613, USCS 0614, USCS 0615, USCS 0616, USCS 0617, USCS 0618, USCS 0619, USCS 0620, USCS 0621, USCS 0622, USCS 0623, USCS 0624, USCS 0625, USCS 0626, USCS 0627, USCS 0628, USCS 0629, USCS 0630, USCS 0631, USCS 0632, USCS 0633, USCS 0634, USCS 0635, USCS 0636, USCS 0637, USCS 0638, USCS 0639, USCS 0640, USCS 0641, USCS 0642, USCS 0643, USCS 0644, USCS 0645, USCS 0646, USCS 0647, USCS 0648, USCS 0649, USCS 0650, USCS 0651, USCS 0652, USCS 0653, USCS 0654, USCS 0655, USCS 0656, USCS 0657, USCS 0658, USCS 0659, USCS 0660, USCS 0661, USCS 0662, USCS 0663, USCS 0664, USCS 0665, USCS 0666, USCS 0667, USCS 0668, USCS 0669, USCS 0670, USCS 0671, USCS 0672, USCS 0673, USCS 0674, USCS 0675, USCS 0676, USCS 0677, USCS 0678, USCS 0679, USCS 0680, USCS 0681, USCS 0682, USCS 0683, USCS 0684, USCS 0685, USCS 0686, USCS 0687, USCS 0688, USCS 0689, USCS 0690, USCS 0691, USCS 0692, USCS 0693, USCS 0694, USCS 0695, USCS 0696, USCS 0697, USCS 0698, USCS 0699, USCS 0700, USCS 0701, USCS 0702, USCS 0703, USCS 0704, USCS 0705, USCS 0706, USCS 0707, USCS 0708, USCS 0709, USCS 0710, USCS 0711, USCS 0712, USCS 0713, USCS 0714, USCS 0715, USCS 0716, USCS 0717, USCS 0718, USCS 0719, USCS 0720, USCS 0721, USCS 0722, USCS 0723, USCS 0724, USCS 0725, USCS 0726, USCS 0727, USCS 0728, USCS 0729, USCS 0730, USCS 0731, USCS 0732, USCS 0733, USCS 0734, USCS 0735, USCS 0736, USCS 0737, USCS 0738, USCS 0739, USCS 0740, USCS 0741, USCS 0742, USCS 0743, USCS 0744, USCS 0745, USCS 0746, USCS 0747, USCS 0748, USCS 0749, USCS 0750, USCS 0751, USCS 0752, USCS 0753, USCS 0754, USCS 0755, USCS 0756, USCS 0757, USCS 0758, USCS 0759, USCS 0760, USCS 0761, USCS 0762, USCS 0763, USCS 0764, USCS 0765, USCS 0766, USCS 0767, USCS 0768, USCS 0769, USCS 0770, USCS 0771, USCS 0772, USCS 0773, USCS 0774, USCS 0775, USCS 0776, USCS 0777, USCS 0778, USCS 0779, USCS 0780, USCS 0781, USCS 0782, USCS 0783, USCS 0784, USCS 0785, USCS 0786, USCS 0787, USCS 0788, USCS 0789, USCS 0790, USCS 0791, USCS 0792, USCS 0793, USCS 0794, USCS 0795, USCS 0796, USCS 0797, USCS 0798, USCS 0799, USCS 0800, USCS 0801, USCS 0802, USCS 0803, USCS 0804, USCS 0805, USCS 0806, USCS 0807, USCS 0808, USCS 0809, USCS 0810, USCS 0811, USCS 0812, USCS 0813, USCS 0814, USCS 0815, USCS 0816, USCS 0817, USCS 0818, USCS 0819, USCS 0820, USCS 0821, USCS 0822, USCS 0823, USCS 0824, USCS 0825, USCS 0826, USCS 0827, USCS 0828, USCS 0829, USCS 0830, USCS 0831, USCS 0832, USCS 0833, USCS 0834, USCS 0835, USCS 0836, USCS 0837, USCS 0838, USCS 0839, USCS 0840, USCS 0841, USCS 0842, USCS 0843, USCS 0844, USCS 0845, USCS 0846, USCS 0847, USCS 0848, USCS 0849, USCS 0850, USCS 0851, USCS 0852, USCS 0853, USCS 0854, USCS 0855, USCS 0856, USCS 0857, USCS 0858, USCS 0859, USCS 0860, USCS 0861, USCS 0862, USCS 0863, USCS 0864, USCS 0865, USCS 0866, USCS 0867, USCS 0868, USCS 0869, USCS 0870, USCS 0871, USCS 0872, USCS 0873, USCS 0874, USCS 0875, USCS 0876, USCS 0877, USCS 0878, USCS 0879, USCS 0880, USCS 0881, USCS 0882, USCS 0883, USCS 0884, USCS 0885, USCS 0886, USCS 0887, USCS 0888, USCS 0889, USCS 0890, USCS 0891, USCS 0892, USCS 0893, USCS 0894, USCS 0895, USCS 0896, USCS 0897, USCS 0898, USCS 0899, USCS 0900, USCS 0901, USCS 0902, USCS 0903, USCS 0904, USCS 0905, USCS 0906, USCS 0907, USCS 0908, USCS 0909, USCS 0910, USCS 0911, USCS 0912, USCS 0913, USCS 0914, USCS 0915, USCS 0916, USCS 0917, USCS 0918, USCS 0919, USCS 0920, USCS 0921, USCS 0922, USCS 0923, USCS 0924, USCS 0925, USCS 0926, USCS 0927, USCS 0928, USCS 0929, USCS 0930, USCS 0931, USCS 0932, USCS 0933, USCS 0934, USCS 0935, USCS 0936, USCS 0937, USCS 0938, USCS 0939, USCS 0940, USCS 0941, USCS 0942, USCS 0943, USCS 0944, USCS 0945, USCS 0946, USCS 0947, USCS 0948, USCS 0949, USCS 0950, USCS 0951, USCS 0952, USCS 0953, USCS 0954, USCS 0955, USCS 0956, USCS 0957, USCS 0958, USCS 0959, USCS 0960, USCS 0961, USCS 0962, USCS 0963, USCS 0964, USCS 0965, USCS 0966, USCS 0967, USCS 0968, USCS 0969, USCS 0970, USCS 0971, USCS 0972, USCS 0973, USCS 0974, USCS 0975, USCS 0976, USCS 0977, USCS 0978, USCS 0979, USCS 0980, USCS 0981, USCS 0982, USCS 0983, USCS 0984, USCS 0985, USCS 0986, USCS 0987, USCS 0988, USCS 0989, USCS 0990, USCS 0991, USCS 0992, USCS 0993, USCS 0994, USCS 0995, USCS 0996, USCS 0997, USCS 0998, USCS 0999, USCS 1000, USCS 1001, USCS 1002, USCS 1003, USCS 1004, USCS 1005, USCS 1006, USCS 1007, USCS 1008, USCS 1009, USCS 1010, USCS 1011, USCS 1012, USCS 1013, USCS 1014, USCS 1015, USCS 1016, USCS 1017, USCS 1018, USCS 1019, USCS 1020, USCS 1021, USCS 1022, USCS 1023, USCS 1024, USCS 1025, USCS 1026, USCS 1027, USCS 1028, USCS 1029, USCS 1030, USCS 1031, USCS 1032, USCS 1033, USCS 1034, USCS 1035, USCS 1036, USCS 1037, USCS 1038, USCS 1039, USCS 1040, USCS 1041, USCS 1042, USCS 1043, USCS 1044, USCS 1045, USCS 1046, USCS 1047, USCS 1048, USCS 1049, USCS 1050, USCS 1051, USCS 1052, USCS 1053, USCS 1054, USCS 1055, USCS 1056, USCS 1057, USCS 1058, USCS 1059, USCS 1060, USCS 1061, USCS 1062, USCS 1063, USCS 1064, USCS 1065, USCS 1066, USCS 1067, USCS 1068, USCS 1069, USCS 1070, USCS 1071, USCS 1072, USCS 1073, USCS 1074, USCS 1075, USCS 1076, USCS 1077, USCS 1078, USCS 1079, USCS 1080, USCS 1081, USCS 1082, USCS 1083, USCS 1084, USCS 1085, USCS 1086, USCS 1087, USCS 1088, USCS 1089, USCS 1090, USCS 1091, USCS 1092, USCS 1093, USCS 1094, USCS 1095, USCS 1096, USCS 1097, USCS 1098, USCS 1099, USCS 1100, USCS 1101, USCS 1102, USCS 1103, USCS 1104, USCS 1105, USCS 1106, USCS 1107, USCS 1108, USCS 1109, USCS 1110, USCS 1111, USCS 1112, USCS 1113, USCS 1114, USCS 1115, USCS 1116, USCS 1117, USCS 1118, USCS 1119, USCS 1120, USCS 1121, USCS 1122, USCS 1123,

CREW & CUSTOMER MAP - TD# 1856232

CONTACTS:
 CALL LOUIS ORTEGA FOR ACCESS THRU GATE
 LOUIS ORTEGA 310-953-1355
 ERIC PERCIC 424-272-6709

CITY OF TORRANCE
 AZALIA 4kV % ROLLING HILL
 2SN-COMM/INDUST M&S UG
 5205 CALLE MAYOR



PROJECT REQUIREMENTS (Y/N)	
EDISON EASEMENT REQUIRED	<input checked="" type="checkbox"/>
PERD 88 REQUIRED	<input checked="" type="checkbox"/>
UC CIVIL ONLY WORK ORDER	<input checked="" type="checkbox"/>
PERMIT REQUIRED	<input checked="" type="checkbox"/>
PERMIT TYPE: PRVT_PROP	
OUTAGE REQUIRED	<input checked="" type="checkbox"/>
OUTAGE DATE: TBD	TIME: TBD
TRAFFIC CONTROL REQUIRED	<input checked="" type="checkbox"/>
PED. TRAFFIC CONTROL REQ'D	<input checked="" type="checkbox"/>
CONVEYANCE LETTER REQ'D	<input checked="" type="checkbox"/>
ENVIRONMENTAL REQUIREMENTS DOCUMENT (ERD) REQUIRED	<input checked="" type="checkbox"/>
CSD 140 (TLM) REQ'D	<input checked="" type="checkbox"/>

T.L.M. DATA:				
SIZE	KVA	CUST	%	LOAD
EXIST. 50	21.4	2	43	%
PROP. 50	35.3	2	71	%
VOLTAGE DROP: 0.89%				
FLICKER FACTOR: 0.00%				
PRI. CIRCUIT: AZALIA 4kV				

- NOTES:
- CUSTOMER TO INSTALL 5" DUCT FROM 856E TO NEW 400A PANEL
 - SCE TO INSTALL 5" RISER ON EXISTING UNISTRUT
 - SCE TO INSTALL 350 CLP FROM 856E TO NEW PANEL
 - SCE TO REMOVE MCM CABLE FROM 856E TO EXITING PANEL
 - SCE TO REMOVE 3"x2" RISER AND ABANDON 3" DUCT
 - NO PERMITS NECESSARY PRIVATE PROPERTY

- CUSTOMER NOTE:
- PLEASE WORK WITH SCE INSPECTOR FOR BOLLARD PLACEMENT

- TD1856232
 EX: 1035856E
 CLASS 4
 50'
- RM: 1 - RSR 3" TO 2" EXTENSION
 - RM: 1 - MTR KWH 30A 120/240 1P 3W
 - RM: 180 - CBL ALL SIZES AL/CU 3/C 600V
 - RM: 15 - CBL ALL SIZES AL/CU 3/C 600V
 - IN: 1 - TM 2-350 & 1-4/0 600V 1P UG TO OH
 - IN: 1 - RSR PVC/STRAP 5" UNISTRUT APP
 - CF: 8" - CM DUCT 5" (POLE TO PL)
 - CF: 2" - CM DUCT FOR EXCAVATION (POLE TO PL)
 - IN: 160' - CBL (2) 350 MCM, (1) 4/0 600V CLP PLEX
 - IN: 1 - CNH HYLUGS PM 2-350 1-4/0 12/16KV 1P
 - IN: 1 - MTR XRANGE CT BAR TO 600/5 120/240 1P 3W

FINAL DESIGN
 APPROVED FOR CONSTRUCTION

DISTRICT 44 - SOUTH BAY	PROJ MGR Fernandez, Jesus Ferr	ENGINEER Hernandez, Viridiana
PROJECT NO 2205606	PHONE 310-502-0457	PHONE 310-502-0457
CREDIT / SERVICE AZALIA 4kV	PRODUCT 1856232-METER & SERVICE CHANGE	ASSOC DESIGN
INVENTORY MAP 35-(B-4D)	J.P.A. NO.	PROPOSED CONSTRUCTION (LOCATION) 5205 CALLE MAYOR TORRANCE CA 90505
DATE 07/07/2021	APPROVED BY I. KNIGHT	CHECKED BY J. FERNANDEZ
TYPE Southern California Edison Company	DRAWN BY V. HERNANDEZ	PAX # 33389
SHEET 2 of 2		DESIGN/DRAWING NO. 1403819_0.01

E
ENGINEERS

CONSULTING ELECTRICAL ENGINEERS
 1238 7th Street, Santa Monica, Ca. 90401
 Tel: (424) 272-6709

BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:
 5205 CALLE MAYOR
 TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.xx.21	ISSUED FOR PLAN CHECK
2	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

PROJECT NO: **21-108**

DRAWN BY: E ENGINEERS CHECKED BY: EP


PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED


SHEET SIZE: 24X36

DRAWING TITLE: **SCE MAP AND DETAILS**

SHEET NO: **E602**



CONSULTING ELECTRICAL ENGINEERS
1238 7th Street, Santa Monica, Ca. 90401
Tel: (424) 272-6709



BDLG. OWNER:

PROJECT:

FIRE STATION 4 RENOVATION

PROJECT ADDRESS:

5205 CALLE MAYOR
TORRANCE, CA 90505

ISSUE OR REVISION NOTES:

NO.	DATE	DESCRIPTION
1	06.02.21	ISSUED FOR REVIEW

The above drawings, specifications, ideas, designs and arrangements represented hereby are and shall remain the property of the designer, and no part thereof shall be copied, disclosed to others or used in connection with any work or project other than the specified project for which they have been prepared and developed without the written consent of the designer. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions.

Written dimensions on these drawings shall have precedence over scaled dimensions. Contractor shall verify and be responsible for all dimensions and conditions on the job and this office must be notified of any variations from the dimensions and conditions shown by these drawings. Shop details must be submitted to the office for approval before proceeding with fabrication.

PROJECT NO: 21-108

DRAWN BY: E ENGINEERS CHECKED BY: EP

PROJECT MANAGER: EP

DRAWING SCALE: AS NOTED

SHEET SIZE: 24x36

DRAWING TITLE:

ELECTRICAL CONSTRUCTION
SPECIFICATIONS

SHEET NO:

E700

ELECTRICAL CONSTRUCTION SPECIFICATIONS

<p>1.00 SCOPE</p> <p>A. FURNISH ALL LABOR AND FURNISH AND INSTALL ALL MATERIALS AND EQUIPMENT FOR A COMPLETE AND OPERATING ELECTRICAL SYSTEM AS SHOWN ON THE DRAWINGS AND/OR SPECIFIED HEREINAFTER.</p> <p>B. REMOVE ABANDONED CONNECTORS, CABLE, RECEPTACLES, TELEPHONE OUTLETS AND ALL OUTLET BOXES, CONDUIT AND WIRE THROUGHOUT THE ENTIRE AREA.</p> <p>C. FURNISH, INSTALL AND CONNECT CONTROL CABLE AND CONNECTORS AS NOTED ON DRAWINGS.</p> <p>D. INSTALL AND CONNECT ALL OWNER FURNISHED EQUIPMENT AS NOTED. COORDINATE WITH OWNER BEFORE INSTALLATION.</p>	<p>1.05 RECORD DRAWINGS</p> <p>A. KEEP UP TO DATE, A COMPLETE SET OF AS BUILT MYLARS TO INDICATE ANY CHANGES FROM THE ORIGINAL DRAWINGS. UPON COMPLETION OF THE INSTALLATION, FURNISH A COMPLETE SET OF AS-BUILT MYLARS. THESE DRAWINGS SHALL BE SUBMITTED TO THE OWNER FOR APPROVAL. AFTER APPROVAL THEY SHALL BECOME THE PROPERTY OF THE OWNER. FINAL PAYMENT WILL BE WITHHELD UNTIL RECEIPT OF THE APPROVED DRAWINGS.</p> <p>1.06 PROTECTION & SAFEGUARDS</p> <p>A. THE CONTRACTOR SHALL ERECT AND MAINTAIN SUITABLE BARRIERS, PROTECTIVE DEVICES, LIGHTS AND WARNING SIGNS WHERE REQUIRED FOR THE PROTECTION OF THE PUBLIC AND EMPLOYEES ABOUT THE BUILDING. HE SHALL BE FULLY RESPONSIBLE FOR ANY LOSS OR INJURY TO PERSONS OR PROPERTY RESULTING FROM HIS NEGLIGENCE OF THESE PRECAUTIONS, HIS OWN CARELESSNESS, OR THE CARELESSNESS OR NEGLIGENCE OF HIS EMPLOYEES, OR HIS SUB-CONTRACTOR AND/OR THEIR EMPLOYEES.</p>	<p>1.13 PANELBOARDS</p> <p>A. LIGHTING PANELBOARDS SHALL BE WESTINGHOUSE TYPE WES 120/208V-3 PHASE AND 480/277V OR EQUAL BY SQUARE D, CUTLER HAMMER, GENERAL ELECTRIC OR SYLVANIA. THE CIRCUIT BREAKERS SHALL BE BOLT ON TYPE AND SHALL HAVE THE NUMBER OF POLES INDICATED ON THE DRAWINGS. THE HANDLES WILL NOT BE ALLOWED. PROVIDE AN ENGRAVED PHENOLIC NAMEPLATE FOR ALL PANELS.</p> <p>1.14 WIRING DEVICES</p> <p>A. THE CATALOG NUMBERS OF ALL WIRING DEVICES, UNLESS OTHERWISE SPECIFIED ARE THOSE OF THE HUBBELL COMPANY, OR AS NOTED TO ESTABLISH THE QUALITY DESIRED. EQUAL EQUIPMENT BY GENERAL ELECTRIC, BRYANT, SIERRA, SLATER, LEVITON OR A&H WILL BE ACCEPTABLE.</p> <p>B. FURNISH AND INSTALL WALL SWITCHES AT EACH LOCATION INDICATED ON THE DRAWINGS. WHERE MORE THAN ONE SWITCH OCCURS AT THE SAME LOCATION, THEY SHALL BE INSTALLED UNDER A MULTIPLE GANG PLATE. SWITCH HANDLE SHALL BE WHITE COLOR. SWITCHES HANDLES SHALL BE WHITE COLOR. SWITCHES SHALL BE A.C. QUIET TYPE RATED 20 AMPERES AT 120 AND/OR 277 VOLTS. - HUBBELL #1221.</p> <p>C. FURNISH AND INSTALL CONVENIENCE RECEPTACLE AT EACH LOCATION INDICATED ON THE DRAWINGS. RECEPTACLE SHALL BE 5262.</p> <p>D. PLATES FOR WIRING DEVICES SHALL BE WHITE OR AS SELECTED BY ARCHITECT.</p>	<p>1.18 CONDUCTORS</p> <p>A. ALL CONDUCTORS SHALL BE COPPER WITH THHN 90 DEGREE C INSULATION.</p> <p>B. CONDUCTORS SHALL BE CONTINUOUS FROM OVER-CURRENT PROTECTIVE DEVICE TO TERMINAL OR FARTHEST OUTLET. NO JOINTS SHALL BE MADE EXCEPT IN PULL, JUNCTION OR OUTLET BOXES.</p> <p>C. JOINTS IN WIRES SMALLER THAN NO.6 SHALL BE MADE WITH IDEAL SUPER WIRE NUTS OR SCOTCH TYPE "R", "Y" OR "B" SPRING CONNECTORS. JOINTS IN WIRES NO. 6 AND LARGER SHALL BE MADE WITH APPROVED SOLDERLESS CONNECTORS. ALL JOINTS IN CABLES NO. 6 AND LARGER SHALL BE INSULATED AND TAPED.</p> <p>D. NEUTRAL CONDUCTORS SHALL NOT BE BROKEN AT ANY DUPLX RECEPTACLE, LIGHTING FIXTURE OR SIMILAR WIRING DEVICE IN MULTI-WIRE (3 WIRE OR 4 WIRE) CIRCUITS. GROUNDED NEUTRAL SHALL NOT DEPEND ON DEVICE CONNECTIONS FOR CONTINUITY. NEUTRAL WIRES CAN BE SPLICED TOGETHER WITH PIGTAIL TO NEUTRAL TERMINAL ON RECEPTACLE, LIGHTING FIXTURE OR SIMILAR DEVICE. IF DEVICE OR FIXTURE IS REMOVED, NEUTRAL WILL REMAIN CONTINUOUS.</p>
<p>1.01 GENERAL</p> <p>A. PROVIDE ALL EQUIPMENT, MATERIAL, LABOR, SERVICE, HOISTING, SUPPORT AND SUPERVISION FOR ALL WORK SHOWN ON THE ELECTRICAL DRAWINGS AND AS SPECIFIED.</p> <p>B. THE ENTIRE WORK PROVIDED SHALL BE CONSTRUCTED AND FINISHED IN EVERY RESPECT IN A WORKMANLIKE AND SUBSTANTIAL MANNER. FURNISH AND INSTALL ALL WORK AS MAY BE NECESSARY TO COMPLETE THE SYSTEMS IN ACCORDANCE WITH THE BEST TRADE PRACTICE AND TO THE SATISFACTION OF THE OWNER. THE ENTIRE INSTALLATION SHALL BE READY IN EVERY RESPECT FOR SATISFACTORY AND EFFICIENT OPERATION WHEN COMPLETE.</p> <p>C. THE DRAWINGS SHOW VARIOUS CONDUIT AND WIRING SYSTEMS SCHEMATICALLY AND PROVIDE CIRCUIT NUMBERS FOR REFERENCE ONLY. BALANCE ALL PANELBOARDS AND RECORD ALL CIRCUIT NUMBERS ON AS-BUILT DRAWINGS.</p> <p>D. SUBMIT A SINGLE GUARANTEE STATING THAT ALL PORTIONS OF THE WORK ARE IN ACCORDANCE WITH CONTRACT REQUIREMENTS. GUARANTEE ALL WORK AGAINST FAULTY AND IMPROPER MATERIAL AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM DATE OF FINAL ACCEPTANCE BY THE OWNER EXCEPT THAT WHERE GUARANTEES OR WARRANTIES FOR LONGER TERMS ARE SPECIFIED BY CONTRACT, SUCH LONGER TERM SHALL APPLY. AT NO ADDITIONAL COST TO THE OWNER, WITHIN 24 HOURS AFTER NOTIFICATION, CORRECT ANY DEFICIENCIES WHICH OCCUR DURING THE GUARANTEE PERIOD, ALL TO THE SATISFACTION OF THE OWNER.</p> <p>E. PROVIDE ALL MATERIAL AND EQUIPMENT AND MAKE THE FINAL CONNECTIONS TO ALL EQUIPMENT.</p>	<p>1.07 SHOP DRAWINGS</p> <p>A. WITHIN THIRTY (30) DAYS AFTER AWARD OF THE GENERAL CONTRACT, THE CONTRACTOR SHALL SUBMIT SIX (6) PRINTS OF ALL REQUIRED SHOP DRAWINGS AND BROCHURES. SHOP DRAWINGS AND BROCHURES WILL BE REQUIRED FOR THE FOLLOWING EQUIPMENT. SWITCHBOARDS, PANELBOARDS, CIRCUIT BREAKERS, LIGHT FIXTURES AND ANY SPECIAL EQUIPMENT. EQUIPMENT INSTALLED WITHOUT APPROVAL THEREOF SHALL BE DONE AT THE RISK OF THE CONTRACTOR AND THE COST FOR REMOVAL OF SUCH EQUIPMENT OR RELATED WORK WHICH IS JUDGED UNSATISFACTORY FOR ANY REASON SHALL BE AT THE EXPENSE OF THIS CONTRACTOR.</p> <p>1.08 EXISTING CONDITIONS</p> <p>A. BEFORE SUBMITTING BID BECOME THOROUGHLY FAMILIAR WITH ACTUAL EXISTING CONDITIONS AT THE BUILDING AND OF THE PRESENT INSTALLATIONS TO WHICH CONNECTIONS MUST BE MADE OR WHICH MUST BE CHANGED OR ALTERED. THE INTENT OF THE WORK IS SHOWN ON THE DRAWINGS AND DESCRIBED HEREINAFTER AND NO CONSIDERATION WILL BE GRANTED BY REASON OF LACK OF FAMILIARITY ON THE PART OF THE CONTRACTOR WITH ACTUAL PHYSICAL CONDITIONS AT THE SITE.</p> <p>B. WHERE SPECIFICALLY CALLED FOR ON THE DRAWING OR WHEN PERMISSION IS SPECIFICALLY GIVEN BY THE OWNER, EXISTING EQUIPMENT AND MATERIAL MAY BE REUSED. SALVAGEABLE MATERIAL, UNLESS OTHERWISE INSTRUCTED BY THE OWNER, SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND BE REMOVED FROM THE SITE.</p>	<p>1.15 OUTLET BOXES</p> <p>A. JUNCTION BOXES SHALL BE 4 BY 4 BY 2-1/8 INCHES DEEP WITH COVERS UNLESS OTHERWISE NOTED OR REQUIRED BY CODE. JUNCTION BOXES ABOVE SUSPENDED CEILINGS FOR LIGHTING AND FOR DATA/COMMUNICATION SYSTEMS SHALL BE 4-11/16 BY 2-1/8 INCHES DEEP MINIMUM, TO BE INSTALLED ADJACENT TO RECESSED FIXTURE IN SUCH MANNER AS TO BE ACCESSIBLE THROUGH THE OPENING IN THE CEILING IN WHICH THE FIXTURE IS INSTALLED.</p> <p>1.16 LIGHTING FIXTURES</p> <p>A. FURNISH AND INSTALL UNDERWRITERS LABORATORIES, INC. LISTED LIGHTING FIXTURES AS INDICATED ON DRAWINGS.</p> <p>B. ALL FIXTURES SHALL BE FURNISHED COMPLETE WITH LAMPS.</p> <p>C. THIS CONTRACTOR SHALL FURNISH AND INSTALL ALL FIXTURE SUPPORTS FOR ALL FIXTURES.</p> <p>D. ALL INCANDESCENT LAMPS SHALL BE INSIDE FROSTED. FLUORESCENT LAMPS SHALL BE STANDARD WARM WHITE (EXCEPT WHERE COLOR SHOWN OTHERWISE); WESTINGHOUSE OR SYLVANIA. INCANDESCENT AND FLUORESCENT LAMPS SHALL BE AS SPECIFIED ABOVE UNLESS OTHERWISE NOTED.</p> <p>E. ALL FLUORESCENT FIXTURE BALLASTS SHALL BE CLASS "P", CAL ENERGY LISTED HIGH POWER FACTOR AND C.B.M. APPROVED. BALLASTS SHALL BE THE QUIETEST TYPE AVAILABLE FOR THE APPLICATION, AND THE CONTRACTOR SHALL REPLACE ALL UNUSUALLY LOUD BALLASTS.</p>	<p>1.19 EQUIPMENT CONNECTIONS</p> <p>A. MAKE CONNECTIONS TO ALL MOTORS, MOTOR CONTROLLERS AND ELECTRICALLY OPERATED EQUIPMENT WHETHER FURNISHED AS A PART OF THIS CONTRACT OR FURNISHED BY THE OWNER FOR INSTALLATION UNDER THIS CONTRACT. FURNISH AND INSTALL ALL CONDUITS AND CONDUCTORS REQUIRED FOR THESE CONNECTIONS AND FOR CONTROL WIRING AS INDICATED BY ELECTRICAL IN OTHER SECTIONS.</p> <p>1.20 DISCONNECT SWITCHES AND CONTROL WIRING</p> <p>A. FURNISH AND INSTALL HORSE POWER RATED DISCONNECT SWITCHES FOR ALL MOTORS, CONTROL CIRCUITS AND OTHER ELECTRICAL EQUIPMENT AS REQUIRED BY CODE WHETHER OR NOT SHOWN ON THE DRAWINGS. A DISCONNECT SWITCH SHALL BE LOCATED WITHIN SIGHT FROM THE CONTROLLER DISCONNECT LOCATION. WHERE A MOTOR IS NOT WITHIN SIGHT FROM THE CONTROLLER DISCONNECT LOCATION AN ADDITIONAL DISCONNECTING SWITCH SHALL BE PROVIDED WITHIN SIGHT OF THE MOTOR LOCATION.</p> <p>B. THE ELECTRICAL CONTRACTOR SHALL VERIFY WITH THE MECHANICAL CONTRACTOR FOR ITEMS, DEVICES OR EQUIPMENT THAT THE ELECTRICAL CONTRACTOR IS TO FURNISH, INSTALL AND/OR CONNECT FOR THE HEATING, VENTILATING, AIR CONDITIONING AND PLUMBING SYSTEM DEVICES UNDER THIS CONTRACT.</p>
<p>1.02 CODES AND PERMITS</p> <p>A. ALL WORK SHALL BE DONE IN FULL COMPLIANCE WITH THE NATIONAL ELECTRIC CODE AND ALL LOCAL CODES OR ORDINANCES HAVING JURISDICTION.</p> <p>B. ALL EQUIPMENT AND MATERIALS SHALL BE NEW EXCEPT WHERE SPECIFICALLY NOTED TO BE REUSED AND LISTED BY THE UNDERWRITER'S LABORATORIES, INC., MANUFACTURED IN ACCORDANCE WITH ASME, NEMA ANSI OR IEEE STANDARDS, AND APPROVED BY ALL AUTHORITIES HAVING JURISDICTION.</p> <p>C. SECURE AND PAY FOR ALL NECESSARY APPROVALS, PERMITS, INSPECTIONS, ETC., AND DELIVER THE OFFICIAL RECORDS OF THE GRANTING OF PERMITS TO THE OWNER WITHOUT ADDITIONAL COST TO THE OWNER.</p>	<p>1.09 CUTTING & PATCHING</p> <p>A. THE CONTRACTOR SHALL DO ALL DRILLING, CUTTING, AND PATCHING OF GENERAL CONSTRUCTION WORK EXISTING OR NEW. ROUGH FINISH AND TRIM WHICH MAY BE REQUIRED FOR THE INSTALLATION OF ALL OF HIS WORK. ALL PATCHING SHALL BE OF THE SAME MATERIALS, WORKMANSHIP AND FINISH AS THE ORIGINAL WORK, AND SHALL ACCURATELY MATCH ALL SURROUNDING WORK.</p> <p>1.10 ELECTRICAL SERVICE</p> <p>A. FURNISH AND INSTALL ALL ELECTRICAL SERVICE CONDUIT, CONDUCTORS, PULL BOXES, METER SOCKETS AND SERVICE SWITCHGEAR. SERVICE FACILITIES AND EQUIPMENT SHALL CONFORM TO THE REQUIREMENTS OF THE UTILITY COMPANY. IMMEDIATELY UPON AWARD OF CONTRACT, CONTACT THE UTILITY COMPANY TO COORDINATE THEIR WORK WITH THE WORK OF THIS CONTRACT. OBTAIN APPROVAL OF THE UTILITY COMPANY FOR SERVICE EQUIPMENT AND CONNECTIONS. ALL SERVICE AND CABLE CHARGES OF THE UTILITY COMPANY WILL BE PAID BY THE CONTRACTOR.</p>	<p>1.17 CONDUIT, EMT AND FITTINGS</p> <p>A. RACEWAYS LARGER THAN 3-INCH SHALL BE GALVANIZED RIGID STEEL UNLESS OTHERWISE SPECIFIED.</p> <p>B. RIGID METAL RACEWAYS SHALL BE INSTALLED IN WET LOCATIONS, IN OR UNDER CONCRETE SLABS ON GRADE WITH OR WITHOUT VAPOR BARRIER, IN CONCRETE WALLS AND COLUMNS, IN CONCRETE SLABS, WALLS AND COLUMNS EXPOSED TO THE WEATHER WITH OR WITHOUT VAPOR BARRIERS; WHERE EXPOSED IN AREAS OPEN TO THE WEATHER, WHERE EXPOSED ON WALLS AND COLUMNS UP 6 FEET ABOVE THE FLOOR, EXCEPT IN ELECTRICAL OR TELEPHONE RISER CLOSETS; AND IN MECHANICAL ROOMS IN SIZES LARGER THAN 1-IN UP TO 7- FEET 0 INCHES ABOVE FINISHED FLOOR.</p> <p>C. ELECTRICAL METALLIC TUBING IN SIZES UP TO 3-INCH MAY BE INSTALLED IN INTERIOR SPACES WHERE RIGID RACEWAY IS NOT REQUIRED, AND WHERE PERMITTED BY THE LOCAL CODE AUTHORITIES HAVING JURISDICTION.</p> <p>D. JOIN ELECTRICAL METALLIC TUBING WITH WATERTIGHT STEEL COMPRESSION TYPE THREADLESS FITTINGS THROUGHOUT. USE CONNECTORS OF FACTORY PRE INSULATED TYPE IN ALL SIZES. EMT FITTINGS USING SET SCREWS ARE NOT ACCEPTABLE. EMT CONNECTIONS SHALL BE OF MALLEABLE IRON OR STEEL.</p> <p>E. FLEXIBLE RACEWAY SHALL BE STEEL AND SHALL BE USED FOR REMOVABLE LIGHTING FIXTURES IN FURRED CEILING SPACES AND AT LOCATIONS AS SHOWN. USE FACTORY PRE INSULATED FITTINGS OF THE TYPE APPROVED AS GROUNDING CONNECTORS. PROVIDE GROUNDING WIRE IN ALL NON-LIQUID TIGHT FLEXIBLE RACEWAY SIZED ACCORDING TO CODE. MAXIMUM LENGTH OF FLEXIBLE RACEWAYS SHALL BE 6- FEET.</p> <p>F. SURFACE RACEWAY SHALL BE WIREMOLD #AL3100. PROVIDE DIVIDER WHERE SHOWN FOR COMBINATION POWER & DATA/COMM.</p>	<p>1.21 TELEPHONE FACILITIES</p> <p>A. TELEPHONE CONDUIT AND FACILITIES SHALL CONFORM TO THE REQUIREMENTS OF THE TELEPHONE COMPANY. IMMEDIATELY UPON AWARD OF CONTRACT, CONTACT THE TELEPHONE COMPANY TO COORDINATE THEIR WORK AND THE WORK OF THIS CONTRACT. TELEPHONE CABLES AND EQUIPMENT WILL BE FURNISHED AND INSTALLED BY THE TELEPHONE COMPANY SECTIONS.</p>
<p>1.03 COORDINATION</p> <p>A. COORDINATE THE WORK OF THIS SECTION WITH THE WORK OF OTHER SECTIONS IN AMPLE TIME FOR THE PROPER INSTALLATION AND CONNECTION AND FOR THE PROVISION OF ALL OPENINGS REQUIRED IN FLOORS AND WALLS.</p> <p>B. CAREFULLY CHECK SPACE REQUIREMENTS WITH OTHER TRADES TO INSURE THAT ALL EQUIPMENT AND MATERIALS CAN BE INSTALLED IN THE SPACES ALLOTTED THERETO. INSTALL ALL WORK TO AVOID OBSTRUCTIONS AND TO PRESERVE HEADROOM AND CEILING HEIGHT REQUIREMENTS.</p> <p>C. CAREFULLY CHECK THE DOCUMENTS WITH OTHER TRADES TO ASCERTAIN THE REQUIREMENTS OF ANY MATERIALS OR EQUIPMENT BEING FURNISHED AND/OR INSTALLED BY THAT SECTION AND PROVIDE THE PROPER INSTALLATION AND/OR CONNECTIONS INCLUDING ANY CONTROL WIRING REQUIRED.</p> <p>D. BEFORE FABRICATION AND INSTALLATION OF SPECIAL SYSTEM OUTLETS VERIFY THE FINAL DESIRED LOCATION OF EQUIPMENT WITH OWNER.</p>	<p>1.11 GROUNDING SYSTEM</p> <p>A. ALL ELECTRICAL EQUIPMENT AND SYSTEMS SHALL BE GROUNDED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE AND TITLE 24, CALIFORNIA ADMINISTRATIVE CODE, PART 3. SERVICE ENTRANCE EQUIPMENT SHALL BE GROUNDED IN ACCORDANCE WITH THE UTILITY COMPANY'S REQUIREMENTS.</p> <p>B. GROUNDING SHALL BE AS INDICATED ON THE DRAWINGS AND BONDED TO THE COLD WATER PIPING SYSTEM.</p> <p>C. PROVIDE A GROUNDING CONDUCTOR WHICH SHALL BE IN ADDITION TO THE CIRCUIT CONDUCTORS INDICATED, IN EACH NONMETALLIC CONDUIT USED FOR LIGHTING AND POWER CIRCUITS.</p> <p>D. ALL SYSTEM GROUNDING CONDUCTORS SHALL BE COPPER. ALL GROUND CONNECTIONS SHALL BE ACCESSIBLE AND MADE WITH COPPER ALLOY FITTINGS.</p>	<p>1.12 DISTRIBUTION SYSTEM</p> <p>A. FURNISH AND INSTALL THE ELECTRICAL DISTRIBUTION SYSTEM COMPLETE INCLUDING FEEDERS, BRANCH CIRCUITS, SWITCHBOARDS, PANELBOARDS, OUTLETS AND WIRING DEVICES.</p>	
<p>1.04 CLEANING PREMISES</p> <p>A. THE CONTRACTOR SHALL KEEP ALL PARTS OF THE BUILDING AND SITE FREE FROM ANY ACCUMULATIONS OF RUBBISH OR WASTE MATERIALS CAUSED BY HIS WORKMEN, AND SHALL REMOVE SUCH ACCUMULATIONS FROM THE BUILDING, SITE AND PROPERTY. JOB SITE SHALL BE CLEANED AT THE END OF EACH WORKING DAY.</p>			

